



SED Diaphragm valve Type: 385 Cast iron Pneumatic operated Single acting, spring closing Internal thread (BSPP) PN10

Characteristics

Type: 385
Norm: EN (DIN)
Housing construction: A (Weir type)
Housing material: Cast iron
Material quality: EN-JL1040
Surface protection: Manufacturer standard
Connection: Internal thread (BSPP)

Characteristics [2]

Standard thread connection: ISO 228-1
Face to Face norm: Manufacturer standard
Actuator: Pneumatic operated
Operating principle: Single acting, spring closing

Membrane material	Nominal inner diameter	Pressure rating	Face to Face length	Actuator material	Minimum medium temperature (continuous)	Maximum medium temperature (continuous)	Maximum pressure difference at 20 °C	Article
			mm		°C	°C	bar	
EPDM	1/2" [15]	PN10	85	PP	-10	80	10	10072014
EPDM	3/4" [20]	PN10	85	PP	-10	80	10	11035665
EPDM	1" [25]	PN10	110	PP	-10	80	10	10053122
EPDM	1.1/4" [32]	PN10	120	PP	-10	80	10	11035666
EPDM	1.1/2" [40]	PN10	140	PP	-10	80	10	10053124
EPDM	2" [50]	PN10	165	PP	-10	80	10	10053123

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.