



SED Diaphragm valve Type: 385 Cast iron Pneumatic operated Single acting, spring closing Flange PN10

Characteristics

Type: 385
Norm: EN (DIN)
Housing construction: A (Weir type)
Housing material: Cast iron
Material quality: EN-JL1040
Surface protection: Manufacturer standard
Connection: Flange

Characteristics (2)

Flange finish: Raised face
Face to Face norm: EN 558, Series 1
Actuator: Pneumatic operated
Operating principle: Single acting, spring closing

Membrane material	Nominal inner diameter	Pressure rating	Face to Face length	Actuator material	Minimum medium temperature (continuous)	Maximum medium temperature (continuous)	Maximum pressure difference at 20 °C	Article
			mm		°C	°C	bar	
EPDM	DN15	PN10	130	PP	-10	80	10	10072016
EPDM	DN25	PN10	160	PP	-10	80	10	10053125
EPDM	DN40	PN10	200	PP	-10	80	10	11035669
EPDM	DN50	PN10	230	PP	-10	80	10	10053126

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.