

CMO Knifegate valve Type: 535 Cast iron Hand wheel Wafer

This product will be phase-out soon by Type: 5402.

Characteristics

Type: 535 Norm: EN (DIN)

Housing construction: 1-part Housing material: Cast iron

Material quality: EN-JL1040

Surface protection: Epoxy coating (in- and external)

Connection: Wafer type

Characteristics (2)

Type of sealing: Uni-directional

Spindle material: 1.4301 Material bracket: Steel

Medium temperature: -10 / 120 °C

Maximum pressure difference at 20 °C: 10 bar

Nominal inner diameter	Pressure rating	Pressure rating flange		Face to Face length mm	Operation	Sealing	Plate material	Primary spindle seal material	Actuator material	Article
DN100	PN10	PN10	Manufacturer standard	50	Hand wheel, non-rising with rising stem	EPDM	1.4301	PTFE/EPDM	Ductile cast iron	11239184
DN125	PN10	PN10	Manufacturer standard	50	Hand wheel, non-rising with rising stem	EPDM	1.4301	PTFE/EPDM	Ductile cast iron	11239185

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

E-mail: valves@eriks.be

Page 1/1

PR_EC011462_0001_MVD_EN_13.05.2024