



TA Regulating valve Series: STAD Type: 26113 Static AMETAL Internal thread (BSPP)

Characteristics

Series: STAD
Type: 26113
Housing material: AMETAL
Material quality: Dezincification resistant brass
Connection: Internal thread (BSPP)
Type of control gear: Static
Application: CH water
With measuring nipples: Yes
Material disc: AMETAL
Spindle material: AMETAL
Material bonnet: AMETAL

Nipple material: AMETAL


Minimum medium temperature (continuous): -20 °C

Maximum medium temperature (continuous): 120 °C

With position indicator: Yes

Application

- Recommended in: Utilities



DN ["]	L mm	H mm	SW mm	Weight [kg]	Kvs-value [m ³ /h]
3/8 *	73	100	22	0,44	1,32
1/2 *	84	100	27	0,47	2,3
3/4 *	94	100	33	0,55	5,37
1	105	105	41	0,68	8,43
1 1/4	121	110	50	1	13,6
1 1/2	126	120	57	1,4	20,2
2	155	120	70	2	31,6

* To use with KOMBI-couplings

Min./Max.	Press./Temp.
Max.operating press.	20bar
Min. Temperature	-20 °C
Max. temperature	120 °C

Nominal inner diameter	Pressure rating	Control range l/h	Kvs value m ³ /h	Kv value m ³ /h	Sealing	Article
1/2" [15]	PN20	120 / 2300	2.3	0.12 / 2.3	EPDM	13416234
3/4" [20]	PN20	520 / 5370	5.37	0.52 / 5.37	EPDM	13416238
1" [25]	PN20	580 / 8430	8.43	0.58 / 8.43	EPDM	13416241
1.1/4" [32]	PN20	1160 / 13600	13.6	1.16 / 13.6	EPDM	13416245
1.1/2" [40]	PN20	1880 / 20200	20.2	1.88 / 20.2	EPDM	13416248
2" [50]	PN20	2440 / 31600	31.6	2.44 / 31.6	EPDM	13416251

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.