



ECON® Regulating valve Type: 2920 Static Cast iron Flange

Characteristics

Type: 2920
Housing material: Cast iron
Material quality: EN-JL1040
Surface protection: Coated
Connection: Flange
Type of control gear: Static
Application: CH water
With measuring nipples: Yes
Material disc: Plastic
Spindle material: Brass
Material bonnet: EN-JS1050

Nipple material: Brass


Minimum medium temperature (continuous): -10 °C

Maximum medium temperature (continuous): 120 °C

With position indicator: Yes

Application

- Recommended in: Utilities



DN [mm]	A mm	D mm	K mm	b mm	c mm	d mm	Dk mm	H mm	L mm	n qty	Weight [kg]
40	200	150	110	3	18	84	74	130	19	4	6.1
50	230	165	125	3	20	99	74	130	19	4	8.3
65	290	185	145	3	20	118	130	205	19	4	12.9
80	310	200	160	3	22	132	130	220	19	8	17.8
100	350	220	180	3	24	156	130	240	19	8	22.7
125	400	250	210	3	26	184	130	260	19	8	34.0
150	480	285	240	3	26	211	130	285	23	8	48.5
200	600	340	295	3	30	266	310	480	23	12	114.5
250	730	405	355	3	32	319	310	525	28	12	159.0
300	850	460	410	4	32	370	310	535	28	12	210.5

Min./Max.	Press/Temp.
Max.oper. pressure	16bar
Min. Temperature	-10°C
Max. temperature	120 °C

Nominal inner diameter	Pressure rating	Control range l/h	Kvs value m³/h	Kv value m³/h	Sealing	Article
DN40	PN16	2730 / 22360	22.36	2.73 / 22.36	EPDM	13389162
DN50	PN16	2660 / 32150	32.15	2.66 / 32.15	EPDM	13033788
DN65	PN16	3600 / 88800	83.3	3.6 / 88.8	EPDM	12711934
DN80	PN16	5900 / 113400	113.4	5.9 / 113.4	EPDM	12605788
DN100	PN16	5600 / 184700	180.5	5.6 / 184.7	EPDM	12711935
DN125	PN16	8300 / 285100	280	8.3 / 285.1	EPDM	12711936
DN150	PN16	7900 / 390200	390.2	7.9 / 390.2	EPDM	12426829
DN200	PN16	27500 / 710000	710	27.5 / 710	EPDM	12711937
DN250	PN16	43500 / 1187500	1187.5	43.5 / 1187.5	EPDM	12711938

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Nominal inner diameter	Pressure rating	Control range l/h	Kvs value m³/h	Kv value m³/h	Sealing	Article
DN300	PN16	44900 / 1504100	1504.1	44.9 / 1504.1	EPDM	12711939

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.