

TA Regulating valve Series: TA-COMPACT-P Type: 26361 Dynamic External thread (BSPP)

Characteristics

Series: TA-COMPACT-P

Type: 26361

Connection: Internal thread (BSPP) Type of control gear: Dynamic

Application: CH water With measuring nipples: Yes

Minimum medium temperature (continuous): -10 °C Maximum medium temperature (continuous): 90 $^{\circ}$ C

Application

• Recommended in: Utilities

Nominal inner diameter	Pressure rating	Type of regulation	Control range	Kvs value	Kv value	Article
			I/h	m³/h	m³/h	
3/8" (10)	PN16	Open-close	90 / 470	0.47	0.09 / 0.47	12712493
1/2" (15)	PN16	Open-close	20 / 120	0.12	0.02 / 0.12	12712494
3/4" (20)	PN16	Open-close	210 / 1150	1.15	0.21 / 1.15	12712495

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

E-mail: valves@eriks.be

Page 1/1

PR_EC011463_0061_FW_EN_18.05.2024