



GF Ball check valve Series: 561 PVC-C Glued sleeve PN16

Characteristics

Series: 561

Construction type: Straight

Housing material: PVC-C

Connection: Glued sleeve

External tube diameter of connection mm	Pressure rating	Valve shape	Sealing	Minimum medium temperature [continuous] °C	Maximum medium temperature [continuous] °C	Article
16	PN16	Ball	EPDM	0	80	12301715
16	PN16	Ball	FPM [FKM]	0	80	12301722
20	PN16	Ball	EPDM	0	80	12301716
20	PN16	Ball	FPM [FKM]	0	80	12301723
25	PN16	Ball	EPDM	0	80	12301717
25	PN16	Ball	FPM [FKM]	0	80	12301724
32	PN16	Ball	EPDM	0	80	12301718
32	PN16	Ball	FPM [FKM]	0	80	12301725
40	PN16	Ball	EPDM	0	80	12301719
40	PN16	Ball	FPM [FKM]	0	80	12301726
50	PN16	Ball	EPDM	0	80	12301720
50	PN16	Ball	FPM [FKM]	0	80	12301727
63	PN16	Ball	EPDM	0	80	12301721
63	PN16	Ball	FPM [FKM]	0	80	12301728

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.