



RITAG Wafer type check valve Type: 2634 Steel Wafer type PN40

Characteristics

Type: 2634

Norm: EN (DIN)

Housing material: Steel


Material quality: 1.4006

Connection: Wafer type

Face to Face norm: EN 558, Series 49

With spring: Yes

Maximum pressure difference at 20 °C: 40 bar



DN	L	d	d1	D1	D2	Weight	Opening press. horizontal flow	Opening press. vert. falling flow	Opening press. vert. rising flow	Opening press. vert. rising flow without spring
[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[kg]	mbar	mbar	mbar	mbar
15	16	51	28	43	15	0.15	20	16	24	4
20	19	61	33	53	20	0.25	20	16	24	4
25	22	71	41.5	64	25	0.3	20	16	24	4
32	28	82	51.5	76	32	0.6	20	16	24	4
40	31.5	92	58.5	86	40	0.8	20	15.5	24.5	4.5
50	40	108	71.5	96	48.5	1.3	20	15	25	5
65	46	127	90	116	63	2	20	14.5	25.5	5.5
80	50	142	110	132	77	2.3	20	13.5	26.5	6.5
100	60	162	126	152	96	3.5	20	13.5	26.5	6.5
125	90	--	161	193	118	8	20	--	34	14
150	106	--	186	218	138	17	20	--	33	13
200	140	--	240	275	194	23	20	--	32	12

For DN15-100 applies D1=PN6 / d=PN10-40 and for DN125-200 applies D1=PN6-40

Nominal inner diameter	Pressure rating	Pressure rating flange	Face to Face length	Valve shape	Sealing	Material disc	Spring material	Minimum medium temperature (continuous)	Maximum medium temperature (continuous)	Article
			mm					°C	°C	
DN65	PN40	PN6/40	46	Disc	Stainless steel	1.4404	1.4571	-10	300	11812999
DN100	PN40	PN6/40	60	Disc	Stainless steel	1.4404	1.4571	-10	300	11813001
DN32	PN40	PN6/40	28	Disc	Stainless steel	1.4404	1.4571	-10	300	11812996

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.