



LEADER Spiral-wound gasket SRI 316L/316L/P/CS EN 1514-2

Characteristics

Series: SRI
Type: Spiral with inside and outside ring
Norm: EN 1514-2
Inside ring material: Stainless steel 316L
Spiral material: Stainless steel 316L
Material filler: Polytetrafluoroethylene (PTFE)
Centring ring material: Carbon steel
Temperature range: -60 / 260 °C

Characteristics [2]

Suitable for medium: Moderate Acids, Pharma, Caustics, Aqueous solutions, Weak Acids, Gases, Acids, Alkalies, Lubricant, Water, Cryogenic, Chemicals, Water (process water), Air (compressed air), Weak Alkalies, Natural gas
Approval according to: EN10.204 3.1, TA-Luft
Spiral ring thickness: 4.5 mm
Inside ring thickness: 3 mm

Flange pressure stage	Nominal diameter	Article
PN10/40	DN25	11152972
PN10/40	DN40	11152973
PN10/40	DN65	12355951
PN10/16	DN150	11908717
PN25/40	DN150	11608460
PN25	DN600	11608461

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.