



LEADER Spiral-wound gasket SRI 316L/316L/C/316L EN 1514-2

Characteristics

Series: SRI

Type: Spiral with inside and outside ring

Norm: EN 1514-2

Inside ring material: Stainless steel 316L

Spiral material: Stainless steel 316L

Material filler: Graphite 98%

Centring ring material: Stainless steel 316L

Temperature range: -200 / 450 °C

Suitable for medium: Gases, Moderate Acids, High pressure steam, Lubricant, Air (compressed air), Water, Steam, Biodiesel, Refrigerants, Chemicals, Cryogenic, Solvents, Weak Acids, Water (process water), Oil, Caustics, Fuel oil, Fuels, Alkalis, Aqueous solutions, Acids, Weak Alkalis, Natural gas, Low pressure steam, Grease, Hydrocarbons

Approval according to: BAM, TA-Luft, Fire safe, EN10.204 3.1

Spiral ring thickness: 4.5 mm

Inside ring thickness: 3 mm

Application

- Recommended in: Chemical

Flange pressure stage	Nominal diameter	Article
PN10/40	DN10	11065794
PN63/160	DN10	11065795
PN10/40	DN15	10002663
PN63/160	DN15	10002715
PN10/40	DN20	10002665
PN10/40	DN25	10002667
PN250	DN25	12652185
PN63/160	DN25	10002717
PN10/40	DN32	10002669
PN63/160	DN32	10002713
PN10/40	DN40	10002671
PN63/160	DN40	10002719
PN10/40	DN50	10002673
PN63	DN50	10002699
PN100/160	DN50	10002679
PN10/40	DN65	10002675
PN63	DN65	10002701
PN100/160	DN65	10002681
PN10/40	DN80	10002677
PN63	DN80	10002703
PN100/160	DN80	10002683
PN10/16	DN100	10002655
PN25/40	DN100	10002693
PN63	DN100	10002705
PN100/160	DN100	10002685
PN10/16	DN125	11065777
PN25/40	DN125	11065778
PN63	DN125	11065779
PN10/16	DN150	10002657
PN25/40	DN150	10002695
PN63	DN150	10002707
PN100/160	DN150	10002687
PN10/16	DN200	10002659
PN25	DN200	10002691
PN40	DN200	10002697

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Flange pressure stage	Nominal diameter	Article
PN63	DN200	10002709
PN100/160	DN200	10002689
PN10	DN250	10002661
PN16	DN250	11065728
PN25	DN250	11065735
PN40	DN250	11065742
PN63	DN250	11065769
PN10	DN300	11065642
PN16	DN300	11065729
PN25	DN300	11065736
PN40	DN300	11065763
PN63	DN300	11065771
PN10	DN350	11065723
PN16	DN350	11065730
PN25	DN350	11065737
PN40	DN350	11065764
PN63	DN350	11065772
PN10	DN400	11065724
PN16	DN400	11065731
PN25	DN400	11065738
PN40	DN400	11065765
PN63	DN400	11065773
PN10	DN450	11065725
PN16	DN450	11065732
PN25	DN450	11065739
PN40	DN450	11065766
PN63	DN450	11065774
PN10	DN500	11065726
PN16	DN500	11065733
PN25	DN500	11065740
PN40	DN500	11065767
PN63	DN500	11065775
PN10	DN600	11065727
PN16	DN600	11065734
PN25	DN600	11065741
PN40	DN600	11065768
PN63	DN600	11065776
PN40	DN700	12560420
PN10	DN800	12560421
PN10	DN900	12560422

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.