

SPIRAX SARCO Thermodynamic steam trap Type 1062 series TD32F stainless steel flange



Characteristics

Series: TD32F

Type: 1062

Construction type: Straight

Connection: Flange



Pressure rating: PN40

Maximum pressure difference: 32 bar

With built-in filter: Yes

Housing material: Stainless steel

Material quality: 1.4021



Application

- Recommended in: Food & Beverages

Type	DN ["/mm]	A [mm]	H mm	L mm	Weight [kg]
1062L - 1062 LA	15	95	55	150	2,3
1062L - 1062 LA	20	105	60	150	3
1062L - 1062 LA	25	115	65	160	4,1
1062H	15	95	55	150	2,4
1062H	20	105	60	150	3,1
1062H	25	115	65	160	4,2
1062HA	15	95	55	150	2,4

Max. pressure		32 bar
Min. pressure		0,25bar (1062L & 1062H)
Min. pressure with anti air-binding disc		0,8 bar (1062LA & 1062HA)
Max. back pressure		80% from inlet pressure
Max. temperature		400°C
Max. temperature with anti air-binding disc		255°C

Nominal inner diameter	Capacity type	With automatic de-aerator	Article
DN15	H	Yes	11811973
DN15	LC	No	11811974
DN20	H	No	11811978

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.