

SPBP

GATES Power band Predator® narrow section SPBP

Characteristics

Series: Predator® Powerband®**Type:** SPBP**Height:** 13 mm**Width (top):** 16 mm**Material:** CR [polychloroprene]**Tensile Cord:** Aramid**Sheathed:** Yes**Temperature resistance:** -30 / 60 °C

Number of ribs	Reference length [ISO]	Article
	mm	Max. 200 articles in the table
6	2120	12066375
6	2650	12066435
6	2800	12066450
6	3150	12066480
6	3350	12066495
6	3550	12066510
6	3750	12066525
6	4000	12066540
6	4250	12066555
6	4500	12066570
6	4750	12066585
6	5000	12066600
6	5300	12066615
6	5600	12066630
6	6000	12066645
7	2120	12066376
7	2240	12066391
7	2360	12066406
7	2500	12066421
7	2650	12066436
7	2800	12066451
7	3000	12066466
7	3150	12066481
7	3350	12066496
7	3550	12066511
7	3750	12066526
7	4000	12066541
7	4250	12066556
7	4500	12066571
7	4750	12066586
7	5000	12066601
7	5300	12066616
7	5600	12066631
7	6000	12066646
8	2120	12066377
8	2240	12066392
8	2360	12066407
8	2500	12066422
8	2650	12066437

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Number of ribs	Reference length (ISO)	Article
	mm	Max. 200 articles in the table
8	2800	12066452
8	3000	12066467
8	3150	12066482
8	3350	12066497
8	3550	12066512
8	3750	12066527
8	4000	12066542
8	4250	12066557
8	4500	12066572
8	4750	12066587
8	5000	12066602
8	5300	12066617
8	5600	12066632
8	6000	12066647
9	2120	12066378
9	2240	12066393
9	2360	12066408
9	2500	12066423
9	2650	12066438
9	2800	12066453
9	3000	12066468
9	3150	12066483
9	3350	12066498
9	3550	12066513
9	3750	12066528
9	4000	12066543
9	4250	12066558
9	4500	12066573
9	4750	12066588
9	5000	12066603
9	5300	12066618
9	5600	12066633
9	6000	12066648
10	2120	12066379
10	2240	12066394
10	2360	12066409
10	2500	12066424
10	2650	12066439
10	2800	12066454
10	3000	12066469
10	3150	12066484
10	3350	12066499
10	3550	12066514
10	3750	12066529
10	4000	12066544
10	4250	12066559
10	4500	12066574
10	4750	12066589
10	5000	12066604
10	5300	12066619
10	5600	12066634
10	6000	12066649
11	2120	12066380

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Number of ribs	Reference length (ISO)	Article
	mm	Max. 200 articles in the table
11	2240	12066395
11	2360	12066410
11	2500	12066425
11	2650	12066440
11	2800	12066455
11	3000	12066470
11	3150	12066485
11	3350	12066500
11	3550	12066515
11	3750	12066530
11	4000	12066545
11	4250	12066560
11	4500	12066575
11	4750	12066590
11	5000	12066605
11	5300	12066620
11	5600	12066635
12	2120	12066381
12	2240	12066396
12	2360	12066411
12	2500	12066426
12	2650	12066441
12	2800	12066456
12	3000	12066471
12	3150	12066486
12	3350	12066501
12	3550	12066516
12	3750	12066531
12	4000	12066546
12	4250	12066561
12	4500	12066576
12	4750	12066591
12	5000	12066606
12	5300	12066621
12	5600	12066636
13	2120	12066382
13	2240	12066397
13	2360	12066412
13	2500	12066427
13	2650	12066442
13	2800	12066457
13	3000	12066472
13	3150	12066487
13	3350	12066502
13	3550	12066517
13	3750	12066532
13	4000	12066547
13	4250	12066562
13	4500	12066577
13	4750	12066592
13	5000	12066607
13	5300	12066622
13	5600	12066637

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Number of ribs	Reference length (ISO)	Article
	mm	Max. 200 articles in the table
14	2120	12066383
14	2240	12066398
14	2360	12066413
14	2500	12066428
14	2650	12066443
14	2800	12066458
14	3000	12066473
14	3150	12066488
14	3350	12066503
14	3550	12066518
14	3750	12066533
14	4000	12066548
14	4250	12066563
14	4500	12066578
14	4750	12066593
14	5000	12066608
14	5300	12066623
14	5600	12066638
15	2120	12066384
15	2240	12066399
15	2360	12066414
15	2500	12066429
15	2650	12066444
15	2800	12066459
15	3000	12066474
15	3150	12066489
15	3350	12066504
15	3550	12066519
15	3750	12066534
15	4000	12066549
15	4250	12066564
15	4500	12066579
15	4750	12066594
15	5000	12066609
15	5300	12066624
15	5600	12066639
16	2120	12066385
16	2240	12066400
16	2360	12066415
16	2500	12066430
16	2650	12066445
16	2800	12066460
16	3000	12066475
16	3150	12066490
16	3350	12066505
16	3550	12066520
16	3750	12066535
16	4000	12066550
16	4250	12066565
16	4500	12066580
16	4750	12066595
16	5000	12066610
16	5300	12066625

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Number of ribs	Reference length (ISO)	Article
	mm	Max. 200 articles in the table
16	5600	12066640

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.