



OPTIBELT V-belt VB classic section Z/10

Characteristics

Series: VB
Type: Z/10
Height: 6 mm
Width (top): 10 mm
Material: Rubber
Tensile Cord: Polyester (PES)
Sheathed: Yes
Shape-toothed model: Yes
Double V-profile model: No
Temperature resistance: -40 / 70 °C

Reference length (ISO)	Inner length	Article
mm	mm	
312	290	23608585
337	315	23608586
397	375	23608587
422	400	23608588
447	425	23608589
472	450	23608590
497	475	23608827
502	480	23608591
522	500	23608592
537	515	23608593
547	525	23608594
552	530	23608595
562	540	23608596
582	560	23608597
597	575	23608598
622	600	23608599
652	630	23608600
672	650	23608601
692	670	23608602
722	700	23608603
732	710	23608604
747	725	23608605
752	730	23608606
772	750	23608607
787	765	23608608
797	775	23608609
822	800	23608610
842	820	23608611
847	825	23608612
872	850	23608613
887	865	23608614
897	875	23608615
922	900	23608616
947	925	23608617
972	950	23608618
997	975	23608619
1022	1000	23608537

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Reference length (ISO)	Inner length	Article
mm	mm	
1038	1016	23608538
1052	1030	23608539
1063	1041	23608540
1072	1050	23608541
1082	1060	23608542
1102	1080	23608543
1122	1100	23608544
1142	1120	23608545
1172	1150	23608546
1187	1165	23608547
1202	1180	23608548
1216	1194	23608549
1237	1215	23608550
1247	1225	23608551
1272	1250	23608553
1292	1270	23608554
1317	1295	23608555
1342	1320	23608556
1368	1346	23608557
1393	1371	23608558
1422	1400	23608559
1444	1422	23608560
1472	1450	23608562
1497	1475	23608563
1522	1500	23608564
1546	1524	23608565
1572	1550	23608566
1597	1575	23608567
1622	1600	23608568
1648	1626	23608569
1673	1651	23608570
1697	1675	23608571
1722	1700	23608572
1747	1725	23608573
1772	1750	23608574
1797	1775	23608575
1822	1800	23608576
1872	1850	23608577
1922	1900	23608578
1997	1975	23608579
2022	2000	23608580
2142	2120	23608581
2262	2240	23608582
2382	2360	23608583
2522	2500	23608584

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.