



OPTIBELT PK multi-ribbed belt

Characteristics

Series: RB

Type: PK

Height: 4.6 mm

Material: CR (polychloroprene)

Tensile Cord: Polyester (PES)

Sheathed: No

Shape-toothed model: No

Double V-profile model: No

Temperature resistance: -40 / 70 °C

Pitch mm	Number of ribs	Effective length (ISO) mm	Reference length (ISO) mm	Article
	3	630	630	12399333
	3	648	648	12399334
	3	800	800	12399338
	3	812	812	23611960
	3	830	830	12399339
	3	913	913	12399356
	3	940	940	23611970
	3	1080	1080	12399361
	3	1090	1090	23611935
	3	1150	1150	23611936
	3	1285	1285	23611938
	4	648	648	12399386
	4	730	730	23612545
	4	775	775	12399391
	4	800	800	23612554
	4	812	812	23612555
	4	890	890	12399397
	4	913	913	12399398
	4	920	920	12399399
	4	940	940	12399401
	4	954	954	12399402
	4	962	962	12399403
	4	990	990	23612586
	4	1080	1080	12399409
	4	1090	1090	12399410
	4	1125	1125	12399413
	4	1165	1165	12399414
	4	1190	1190	12399418
	4	1230	1230	12399420
	4	1245	1245	12399421
	4	1520	1520	12399423
	4	2170	2170	12022150
	5	630	630	23613118
	5	698	698	12399438
	5	775	775	12399440
	5	800	800	23613129
	5	830	830	12399443
	5	875	875	23613139

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Pitch mm	Number of ribs	Effective length (ISO) mm	Reference length (ISO) mm	Article
	5	890	890	12399447
	5	913	913	23613145
	5	920	920	12399448
	5	940	940	12399449
	5	954	954	12399450
	5	962	962	23613153
	5	990	990	23613157
	5	1015	1015	12021774
	5	1080	1080	12399453
	5	1090	1090	12399454
	5	1125	1125	12399456
	5	1165	1165	12399459
	5	1190	1190	12399462
	5	1200	1200	12399463
	5	1270	1270	12399470
	5	1290	1290	12399472
	5	1330	1330	12399475
	5	1345	1345	12399476
	5	1460	1460	23613109
	5	1885	1885	12399495
	6	698	698	12399510
	6	730	730	12399511
	6	865	865	12399519
	6	875	875	23613702
	6	890	890	23613704
	6	913	913	12399520
	6	920	920	23613709
	6	962	962	12399523
	6	1080	1080	23613578
	6	1090	1090	12399530
	6	1125	1125	12399532
	6	1165	1165	12399535
	6	1190	1190	12399538
	6	1200	1200	23613593
	6	1230	1230	12399542
	6	1245	1245	12399544
	6	1270	1270	12399546
	6	1285	1285	12399547
	6	1290	1290	12399548
	6	1345	1345	12399555
	6	1460	1460	12399573
	6	1560	1560	12399579
	6	1570	1570	12399581
	6	1655	1655	12399586
	6	1690	1690	12399589
	6	1755	1755	23613633
	6	1885	1885	12399605
	6	1980	1980	12399615
	6	2030	2030	12399619
	6	2050	2050	12399620
	6	2080	2080	12399624
	6	2120	2120	12399625
	6	2145	2145	12399627

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Pitch mm	Number of ribs	Effective length (ISO) mm	Reference length (ISO) mm	Article
	6	2170	2170	12399630
	6	2255	2255	12399635
	6	2460	2460	12399643
	7	920	920	12399675
	7	1290	1290	12399689
	7	1570	1570	23613981
	7	1980	1980	12399714
	8	1755	1755	23614367
	9	1200	1200	23614576
	9	1290	1290	23614577
3.56	4	830	830	23612558
3.56	4	865	865	23612565
3.56	4	875	875	12399396
3.56	5	812	812	23613130

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.