



OPTIBELT Automotive ribbed belt profile 5 PK

Characteristics

Series: V-Ribbed

Type: PK

Height: 4.6 mm

Material: Rubber

Tensile Cord: Polyester

Pitch mm	Number of ribs	Effective length (ISO) mm	Reference length (ISO) mm	Article
3.56	5	580	580	12399436
3.56	5	655	655	12399437
3.56	5	770	770	12399439
3.56	5	805	805	12399441
3.56	5	812	812	12399442
3.56	5	860	860	12399444
3.56	5	1104	1104	12399455
3.56	5	1145	1145	12399457
3.56	5	1150	1150	12399458
3.56	5	1180	1180	12399461
3.56	5	1210	1210	12399464
3.56	5	1219	1219	12399465
3.56	5	1230	1230	12399466
3.56	5	1255	1255	12399467
3.56	5	1260	1260	12399468
3.56	5	1280	1280	12399471
3.56	5	1310	1310	12399474
3.56	5	1355	1355	12399477
3.56	5	1378	1378	12399479
3.56	5	1390	1390	12399480
3.56	5	1435	4535	12399481
3.56	5	1515	1515	12399482
3.56	5	1545	1545	12399483
3.56	5	1570	1570	12399484
3.56	5	1645	1645	12399485
3.56	5	1680	1680	12399486
3.56	5	1715	1715	12399487
3.56	5	1720	1720	12399489
3.56	5	1745	1745	12399490
3.56	5	1750	1750	12399491
3.56	5	1765	1765	12399492
3.56	5	1800	1800	12399493
3.56	5	1850	1850	12399494
3.56	5	2020	2020	12399496
3.56	5	2030	2030	12399497
3.56	5	2063	2063	12399498

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.