

FENNER Wedge belt Ultra PLUS wrapped narrow section SPC



Fenner
®

Ultra PLUS
Medium duty, wrapped wedge belt

Designed for use in single or multi-belt drives, Fenner® Ultra PLUS transmission belts deliver maximum cost and performance benefits by utilising low elongation polyester cords and abrasion resistant impregnated jacket fabric.

Characteristics

Series: Ultra PLUS

Type: SPC

Height: 18 mm

Width (top): 22 mm

Material: CR (polychloroprene)

Tensile Cord: Polyester (PES)

Sheathed: Yes

Shape-toothed model: No

Double V-profile model: No

With perforation: 0

With top layer: No

Temperature resistance: -55 / 70 °C

Execution

- Ideal for use in single or multi-belt drives ► One-shot tensioning for fit and forget reliability

Approval

- Fully approved by all international standards
 - BS 3790 (British Standard) ► ISO 4184 (International Standards Organisation) ► DIN 7753 (German Institute for Standardization) ► Static conductive in accordance with ISO 1813 ► Conforms to API (American Petroleum Institute) specifications

Technical Information

- Extended temperature range -55° to +70°C. ► PB® (Precision Built) technology, eliminating the need for matching ► Conditionally oil resistant

Reference length (ISO) mm	Article
2000	13919195
2120	13919205
2240	13919216
2360	13919227
2500	13919239
2650	13919254
2800	13919268
3000	13919285
3150	13919300
3350	13919319
3750	13919355
4000	13919372
4250	13919388
4500	13919403
4750	13919419
5000	13919432
5600	13919457
6000	13919466
6300	13919475

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Reference length (ISO)	Article
mm	
6700	13919483
7100	13919494
7500	13919501
8500	13919519

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.