



NORGREN Compact air bellow single acting series PM/31000

- Frictionless operation
- No maintenance or lubrication
- Ideal for short stroke, high-force applications
- High vibration isolation level
- Easy, compact installation

Characteristics

Series: PM/31000

Function: Single acting

Magnetic: No

Operating temperature: -30 / 50 °C

Manufacturer ID	Stroke length mm	Port Size in	Operating pressure bar	Article
PM/31041	40	G3/8	0 / 8	11575565
PM/31042	80	G3/8	0 / 8	11611750
PM/31061	55	G1/2	0 / 8	11575567
PM/31062	115	G1/2	0 / 8	11575569
PM/31081	95	G3/4	0 / 8	11575571
PM/31082	185	G3/4	0 / 8	11575572
PM/31091	105	G3/4	0 / 8	11575573
PM/31092	230	G3/4	0 / 8	11575574
PM/31121	105	G3/4	0 / 8	11575575
PM/31122	215	G3/4	0 / 8	11575576
PM/31021	20	G1/4	0 / 8	11575562
PM/31022	45	G1/4	0 / 8	11575563
PM/31023	65	G1/4	0 / 8	11575564
PM/31123	320	G3/4	0 / 8	11575577

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.