



NORGREN ISO Roundline cylinder double acting series RM/8000/MC

- Magnetic piston as standard
- Conforms to ISO 6432
- High strength, double crimped end cap design
- Corrosion resistant
- Buffer or adjustable cushioning
- Nose mounting nut and piston rod locknut as standard

Characteristics

Series: RM/8000/M

Function: Double acting

Magnetic: Yes

Barrel material: Stainless steel

Operating temperature: -10 / 80 °C

Manufacturer ID	Cushioning	Bore diameter	Stroke length	Port Size	Port Size	Operating pressure	Article
		mm	mm	mm	in		
RM/8016/MC/10	Mechanical	16	10	M 5		1 / 10	11578977
RM/8016/MC/25	Mechanical	16	25	M 5		1 / 10	11578979
RM/8016/MC/40	Mechanical	16	40	M 5		1 / 10	11578980
RM/8016/MC/50	Mechanical	16	50	M 5		1 / 10	11578981
RM/8016/MC/200	Mechanical	16	200	M 5		1 / 10	11578978
RM/8020/MC/10	Mechanical	20	10		G1/8	1 / 10	11579039
RM/8020/MC/160	Mechanical	20	160		G1/8	1 / 10	11579040
RM/8025/MC/25	Mechanical	25	25		G1/8	1 / 10	11579124

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.