



NORGREN Clamping cylinder single acting series M/50100

- Enable high thrusts to be achieved in restricted space
- Neat, clean appearance
- One-piece body construction

Characteristics

Series: M/50100

Function: Single acting

Barrel material: Anodised aluminium

Operating temperature: -10 / 70 °C

Manufacturer ID	Cushioning	Bore diameter	Stroke length	Port Size	Port Size	Operating pressure	Article
		mm	mm	mm	in		
M/50108/4	Without	8	4	M 5		2 / 10	11580269
M/50112/4	Without	12	4	M 5		2 / 10	11580271
M/50112/10	Without	12	10	M 5		2 / 10	11580270
M/50120/4	Without	20	4	M 5		2 / 10	11580273
M/50120/10	Without	20	10	M 5		2 / 10	11580272
M/50132/5	Without	32	5		G1/8	2 / 10	11580276
M/50132/10	Without	32	10		G1/8	2 / 10	11580274
M/50132/25	Without	32	25		G1/8	2 / 10	11580275
M/50150/10	Without	50	10		G1/4	2 / 10	11580277
M/50150/25	Without	50	25		G1/4	2 / 10	11580278
M/50163/10	Without	63	10		G1/4	2 / 10	11580279
M/50163/25	Without	63	25		G1/4	2 / 10	11580280

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.