

AVENTICS Profile cylinder ISO 15552 PRA series

Characteristics

Series: PRA
Function: Double acting
Operating temperature: -20 / 80 °C



Manufacturer ID	Cushioning	Bore diameter mm	Stroke length mm	Port Size in	Operating pressure bar	Article
0822352002						23850099
0822352011						23575432
0822351011						11303490
0822353002						12099407
0822350003						24104684
0822120001	Pneumatic	32	25	G1/8	1.5 / 10	12508706
0822120002	Pneumatic	32	50	G1/8	1.5 / 10	12041951
0822120003	Pneumatic	32	80	G1/8	1.5 / 10	24104626
0822120007	Pneumatic	32	200	G1/8	1.5 / 10	12258902
0822120008	Pneumatic	32	250	G1/8	1.5 / 10	12378902
0822120010	Pneumatic	32	400	G1/8	1.5 / 10	12378915
0822121001	Pneumatic	40	25	G1/4	1.5 / 10	12378900
0822121002	Pneumatic	40	50	G1/4	1.5 / 10	24104628
0822121004	Pneumatic	40	100	G1/4	1.5 / 10	12378914
0822121008	Pneumatic	40	250	G1/4	1.5 / 10	12378926
0822121011	Pneumatic	40	500	G1/4	1.5 / 10	12224398
0822122004	Pneumatic	50	100	G1/4	1.5 / 10	12155004
0822122006	Pneumatic	50	160	G1/4	1.5 / 10	12690381
0822122007	Pneumatic	50	200	G1/4	1.5 / 10	12486044
0822122008	Pneumatic	50	250	G1/4	1.5 / 10	24104630
0822123001	Pneumatic	63	25	G3/8	1.5 / 10	24104632
0822123010	Pneumatic	63	400	G3/8	1.5 / 10	24104634
0822124005	Pneumatic	80	125	G3/8	1.5 / 10	12474211
0822124006	Pneumatic	80	160	G3/8	1.5 / 10	12489927

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.