

AVENTICS Tie rod cylinder ISO 15552 Series TRB



Characteristics

Series: TRB

Function: Double acting

Operating temperature: -20 / 80 °C

Manufacturer ID	Cushioning	Bore diameter mm	Stroke length mm	Port Size in	Operating pressure bar	Article
0822240003						24104641
0822242002						24104647
0822243006						11303379
0822242004						23575424
0822240011						11659337
0822340006	Pneumatic	32	160	G1/8	1.5 / 10	11935601
0822341001	Pneumatic	40	25	G1/4	1.5 / 10	24104667
0822341002	Pneumatic	40	50	G1/4	1.5 / 10	24104668
0822341003	Pneumatic	40	80	G1/4	1.5 / 10	24104669
0822341004	Pneumatic	40	100	G1/4	1.5 / 10	23575428
0822341006	Pneumatic	40	160	G1/4	1.5 / 10	24104670
0822341007	Pneumatic	40	200	G1/4	1.5 / 10	24104671
0822342003	Pneumatic	50	80	G1/4	1.5 / 10	23850174
0822342004	Pneumatic	50	100	G1/4	1.5 / 10	23850175
0822342007	Pneumatic	50	200	G1/4	1.5 / 10	12140433
0822342011	Pneumatic	50	500	G1/4	1.5 / 10	11758274
0822343003	Pneumatic	63	80	G3/8	1.5 / 10	23575429
0822344009	Pneumatic	80	320	G3/8	1.5 / 10	24104678
0822345504	Pneumatic	100	100	G1/2	1.5 / 10	12962719
0822306208	Pneumatic	125	250	G1/2	1.5 / 10	12404976

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.