

CONTARINI DA Cylinder HM5

Characteristics



Type: HM5

Type (DA/SA): Double acting

Max. operating pressure: 250 bar

Front fixation: Fork

Rear fixation: Eye

Bore mm	Number of extensions	Outer diameter piston rod mm	Stroke mm	Built-in size mm	Oilports	Article
32	1	20	50	214	1/4" BSP	12361373
32	1	20	100	264	1/4" BSP	12361374
32	1	20	150	314	1/4" BSP	12361375
32	1	20	200	364	1/4" BSP	12361377
32	1	20	250	414	1/4" BSP	12361378
32	1	20	300	464	1/4" BSP	12361379
32	1	20	400	564	1/4" BSP	12361380
32	1	20	500	664	1/4" BSP	12361381
40	1	20	100	289	1/4" BSP	12361399
40	1	20	150	339	1/4" BSP	12361401
40	1	20	200	389	1/4" BSP	12361406
40	1	20	250	439	1/4" BSP	12361409
40	1	20	300	489	1/4" BSP	12361410
40	1	20	350	539	1/4" BSP	12361411
40	1	20	400	589	1/4" BSP	12361412
40	1	20	450	639	1/4" BSP	12361413
40	1	20	500	689	1/4" BSP	12361414
40	1	25	100	289	1/4" BSP	12361415
40	1	25	150	339	1/4" BSP	12361416
40	1	25	200	389	1/4" BSP	12361417
40	1	25	250	439	1/4" BSP	12361418
40	1	25	300	489	1/4" BSP	12361419
40	1	25	350	539	1/4" BSP	12361420
40	1	25	400	589	1/4" BSP	12361421
40	1	25	450	639	1/4" BSP	12361422
40	1	25	500	689	1/4" BSP	12361423
40	1	25	550	739	1/4" BSP	12361424
40	1	25	600	789	1/4" BSP	12361425
50	1	25	100	310	3/8" BSP	12361426
50	1	25	150	360	3/8" BSP	12361427
50	1	25	200	410	3/8" BSP	12361428
50	1	25	250	460	3/8" BSP	12361429
50	1	25	300	510	3/8" BSP	12361430
50	1	25	350	560	3/8" BSP	12361431
50	1	25	400	610	3/8" BSP	12361432
50	1	25	450	660	3/8" BSP	12361433
50	1	25	500	710	3/8" BSP	12361434
50	1	25	550	760	3/8" BSP	12361435
50	1	25	600	810	3/8" BSP	12361436
50	1	25	700	910	3/8" BSP	12953478
50	1	25	800	1,010	3/8" BSP	12361437
50	1	25	1000	1,210	3/8" BSP	12361438

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Bore mm	Number of extensions	Outer diameter piston rod mm	Stroke mm	Built-in size mm	Oilports	Article
50	1	30	100	310	3/8" BSP	12953480
50	1	30	150	360	3/8" BSP	12361439
50	1	30	200	410	3/8" BSP	12361440
50	1	30	250	460	3/8" BSP	12361441
50	1	30	300	510	3/8" BSP	12361442
50	1	30	350	560	3/8" BSP	12361443
50	1	30	400	610	3/8" BSP	12361444
50	1	30	450	660	3/8" BSP	12361445
50	1	30	500	710	3/8" BSP	12361446
50	1	30	550	760	3/8" BSP	12361447
50	1	30	600	810	3/8" BSP	12361448
50	1	30	700	910	3/8" BSP	12361449
50	1	30	800	1,010	3/8" BSP	12361450
50	1	30	1000	1,210	3/8" BSP	12361451
60	1	30	100	340	3/8" BSP	12361452
60	1	30	150	390	3/8" BSP	12361453
60	1	30	200	440	3/8" BSP	12361454
60	1	30	250	490	3/8" BSP	12361455
60	1	30	300	540	3/8" BSP	12361456
60	1	30	350	590	3/8" BSP	12361457
60	1	30	400	640	3/8" BSP	12361458
60	1	30	450	690	3/8" BSP	12361459
60	1	30	500	740	3/8" BSP	12361460
60	1	30	550	790	3/8" BSP	12361461
60	1	30	600	840	3/8" BSP	12361462
60	1	30	700	940	3/8" BSP	12953479
60	1	30	800	1,040	3/8" BSP	12361463
60	1	30	1000	1,240	3/8" BSP	12361464
60	1	35	100	340	3/8" BSP	12361465
60	1	35	150	390	3/8" BSP	12361466
60	1	35	200	440	3/8" BSP	12361467
60	1	35	250	490	3/8" BSP	12361468
60	1	35	300	540	3/8" BSP	12361469
60	1	35	350	590	3/8" BSP	12361470
60	1	35	400	640	3/8" BSP	12361471
60	1	35	450	690	3/8" BSP	12361472
60	1	35	500	740	3/8" BSP	12361473
60	1	35	550	790	3/8" BSP	12361474
60	1	35	600	840	3/8" BSP	12361475
60	1	35	700	940	3/8" BSP	12953481
60	1	35	800	1,040	3/8" BSP	12361476
60	1	35	1000	1,240	3/8" BSP	12361477
60	1	40	200	440	3/8" BSP	12361478
60	1	40	250	490	3/8" BSP	12361480
60	1	40	300	540	3/8" BSP	12361481
60	1	40	350	590	3/8" BSP	12361482
60	1	40	400	640	3/8" BSP	12361483
60	1	40	450	690	3/8" BSP	12361484
60	1	40	500	740	3/8" BSP	12361485
60	1	40	550	790	3/8" BSP	12361486
60	1	40	600	840	3/8" BSP	12361487
60	1	40	700	940	3/8" BSP	12953482

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Bore mm	Number of extensions	Outer diameter piston rod mm	Stroke mm	Built-in size mm	Oilports	Article
60	1	40	800	1,040	3/8" BSP	12361488
60	1	40	1000	1,240	3/8" BSP	12361489
63	1	40	200	440	3/8" BSP	12361382
63	1	40	250	490	3/8" BSP	12361383
63	1	40	300	540	3/8" BSP	12361384
63	1	40	350	590	3/8" BSP	12361385
63	1	40	400	640	3/8" BSP	12361386
63	1	40	450	690	3/8" BSP	12361387
63	1	40	500	740	3/8" BSP	12361388
63	1	40	550	790	3/8" BSP	12361389
63	1	40	600	840	3/8" BSP	12361390
63	1	40	700	940	3/8" BSP	12953487
63	1	40	800	1,040	3/8" BSP	12361391
63	1	40	1000	1,240	3/8" BSP	12361392
70	1	35	100	340	3/8" BSP	12361490
70	1	35	150	390	3/8" BSP	12361491
70	1	35	150	390	3/8" BSP	12953489
70	1	35	200	440	3/8" BSP	12361492
70	1	35	250	490	3/8" BSP	12361493
70	1	35	300	540	3/8" BSP	12361494
70	1	35	350	590	3/8" BSP	12361495
70	1	35	400	640	3/8" BSP	12361496
70	1	35	450	690	3/8" BSP	12361497
70	1	35	500	740	3/8" BSP	12361498
70	1	35	550	790	3/8" BSP	12361499
70	1	35	600	840	3/8" BSP	12361500
70	1	35	700	940	3/8" BSP	12953483
70	1	35	800	1,040	3/8" BSP	12361501
70	1	35	1000	1,240	3/8" BSP	12361502
70	1	40	200	440	3/8" BSP	12361503
70	1	40	250	490	3/8" BSP	12361504
70	1	40	300	540	3/8" BSP	12361505
70	1	40	350	590	3/8" BSP	12361506
70	1	40	400	640	3/8" BSP	12361507
70	1	40	450	690	3/8" BSP	12361508
70	1	40	500	740	3/8" BSP	12361509
70	1	40	550	790	3/8" BSP	12361510
70	1	40	600	840	3/8" BSP	12361511
70	1	40	700	940	3/8" BSP	12953490
70	1	40	800	1,040	3/8" BSP	12361512
70	1	40	1000	1,240	3/8" BSP	12361513
80	1	40	200	475	BSP female 1/2" BSP	12361514
80	1	40	250	525	BSP female 1/2" BSP	12361515
80	1	40	300	575	BSP female 1/2" BSP	12361516
80	1	40	400	675	BSP female 1/2" BSP	12361517
80	1	40	500	775	BSP female 1/2" BSP	12361518
80	1	40	600	875	BSP female 1/2" BSP	12361519
80	1	40	700	975	BSP female 1/2" BSP	12953484
80	1	40	800	1,075	BSP female 1/2" BSP	12361520
80	1	40	1000	1,275	BSP female 1/2" BSP	12361521
80	1	50	100	1,275	BSP female 1/2" BSP	12361529
80	1	50	200	475	BSP female 1/2" BSP	12361522

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Bore mm	Number of extensions	Outer diameter piston rod mm	Stroke mm	Built-in size mm	Oilports	Article
80	1	50	250	525	BSP female 1/2" BSP	12361523
80	1	50	300	575	BSP female 1/2" BSP	12361524
80	1	50	400	675	BSP female 1/2" BSP	12361525
80	1	50	500	775	BSP female 1/2" BSP	12361526
80	1	50	600	875	BSP female 1/2" BSP	12361527
80	1	50	700	975	BSP female 1/2" BSP	12953491
80	1	50	800	1,075	BSP female 1/2" BSP	12361528
90	1	50	300	616	BSP female 1/2" BSP	12361393
90	1	50	400	716	BSP female 1/2" BSP	12361394
90	1	50	500	816	BSP female 1/2" BSP	12361395
90	1	50	600	916	BSP female 1/2" BSP	12361396
90	1	50	700	1,016	BSP female 1/2" BSP	12953485
90	1	50	800	1,116	BSP female 1/2" BSP	12361397
90	1	50	1000	1,316	BSP female 1/2" BSP	12361398
100	1	35	100	310	3/8" BSP	12953488
100	1	60	300	640	BSP female 1/2" BSP	12361538
100	1	60	400	740	BSP female 1/2" BSP	12361539
100	1	60	500	840	BSP female 1/2" BSP	12361540
100	1	60	600	940	BSP female 1/2" BSP	12361541
100	1	60	700	1,040	BSP female 1/2" BSP	12953492
100	1	60	800	1,140	BSP female 1/2" BSP	12361542
100	1	60	1000	1,340	BSP female 1/2" BSP	12361543
100	1	50	200	540	BSP female 1/2" BSP	12361530
100	1	50	250	590	BSP female 1/2" BSP	12361531
100	1	50	300	640	BSP female 1/2" BSP	12361532
100	1	50	400	740	BSP female 1/2" BSP	12361533
100	1	50	500	840	BSP female 1/2" BSP	12361534
100	1	50	600	940	BSP female 1/2" BSP	12361535
100	1	50	700	1,040	BSP female 1/2" BSP	12953486
100	1	50	800	1,140	BSP female 1/2" BSP	12361536
100	1	50	1000	1,340	BSP female 1/2" BSP	12361537

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.