

CONTARINI DA Cylinder HM0LM



Characteristics

Type: HM0LM

Type (DA/SA): Double acting

Max. operating pressure: 180 bar

Front fixation: None

Rear fixation: None

Bore mm	Number of extensions	Outer diameter piston rod mm	Stroke mm	Built-in size mm	Oilports	Article
40	1	20	100	195	1/4" BSP	12360966
40	1	20	150	245	1/4" BSP	12360967
40	1	20	200	295	1/4" BSP	12360968
40	1	20	250	345	1/4" BSP	12360969
40	1	20	300	395	1/4" BSP	12360970
40	1	20	500	595	1/4" BSP	12360974
40	1	25	100	195	1/4" BSP	12360975
40	1	25	150	245	1/4" BSP	12360976
40	1	25	200	295	1/4" BSP	12360977
40	1	25	250	345	1/4" BSP	12360978
40	1	25	300	395	1/4" BSP	12360979
40	1	25	400	495	1/4" BSP	12360981
40	1	25	500	595	1/4" BSP	12360983
50	1	25	100	205	3/8" BSP	12360984
50	1	25	150	255	3/8" BSP	12360985
50	1	25	200	305	3/8" BSP	12360988
50	1	25	250	355	3/8" BSP	12360989
50	1	25	300	405	3/8" BSP	12360990
50	1	25	500	605	3/8" BSP	12360994
50	1	30	100	205	3/8" BSP	12360995
50	1	30	150	255	3/8" BSP	12360996
50	1	30	200	305	3/8" BSP	12360997
50	1	30	250	355	3/8" BSP	12360998
50	1	30	300	405	3/8" BSP	12360999
50	1	30	500	605	3/8" BSP	12361003
60	1	30	100	220	3/8" BSP	12361004
60	1	30	150	270	3/8" BSP	12361005
60	1	30	200	320	3/8" BSP	12361006
60	1	30	250	370	3/8" BSP	12361007
60	1	30	300	420	3/8" BSP	12361008
60	1	35	100	220	3/8" BSP	12361013
60	1	35	150	270	3/8" BSP	12361014
60	1	35	300	420	3/8" BSP	12361017
60	1	35	400	520	3/8" BSP	12361019
60	1	35	500	620	3/8" BSP	12361021
70	1	35	100	220	3/8" BSP	12361022
70	1	35	150	270	3/8" BSP	12361023
70	1	35	200	320	3/8" BSP	12361024
70	1	35	250	370	3/8" BSP	12361025
70	1	35	300	420	3/8" BSP	12361026
70	1	35	400	520	3/8" BSP	12361028
70	1	40	200	320	3/8" BSP	12361030

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Bore mm	Number of extensions	Outer diameter piston rod mm	Stroke mm	Built-in size mm	Oilports	Article
70	1	40	250	370	3/8" BSP	12361031
70	1	40	300	420	3/8" BSP	12361032
70	1	40	400	520	3/8" BSP	12361034
70	1	40	500	620	3/8" BSP	12361035

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.