

CONTARINI Standard welded cylinder HM0LM05002



Characteristics

Type: HMS

Type (DA/SA): Double acting

Max. operating pressure: 250 bar

Front fixation: Base plate

Rear fixation: Plate on side

Bore mm	Number of extensions	Outer diameter piston rod mm	Stroke mm	Built-in size mm	Oilports	Article
40	1	25	200	369	3/8" BSP	12953383
40	1	25	300	469	3/8" BSP	12953384
40	1	25	400	569	3/8" BSP	12953385
40	1	25	500	669	3/8" BSP	12953386
40	1	25	600	769	3/8" BSP	12953387
50	1	30	200	369	3/8" BSP	12953388
50	1	30	300	469	3/8" BSP	12953389
50	1	30	400	569	3/8" BSP	12953390
50	1	30	500	669	3/8" BSP	12953391
50	1	30	600	769	3/8" BSP	12953392
60	1	35	200	371	3/8" BSP	12953393
60	1	35	300	471	3/8" BSP	12953394
60	1	35	400	571	3/8" BSP	12953395
60	1	35	500	671	3/8" BSP	12953396
60	1	35	600	771	3/8" BSP	12953397
60	1	40	200	371	3/8" BSP	12953398
60	1	40	300	471	3/8" BSP	12953399
60	1	40	400	571	3/8" BSP	12953400
60	1	40	500	671	3/8" BSP	12953401
60	1	40	600	771	3/8" BSP	12953402
70	1	40	200	410	BSP female 1/2" BSP	12953403
70	1	40	300	510	BSP female 1/2" BSP	12953404
70	1	40	400	610	BSP female 1/2" BSP	12953405
70	1	40	500	710	BSP female 1/2" BSP	12953406
70	1	40	600	810	BSP female 1/2" BSP	12953407
70	1	50	200	410	BSP female 1/2" BSP	12953408
70	1	50	300	510	BSP female 1/2" BSP	12953409
70	1	50	400	610	BSP female 1/2" BSP	12953410
70	1	50	500	710	BSP female 1/2" BSP	12953411
70	1	50	600	810	BSP female 1/2" BSP	12953412
80	1	40	200	410	BSP female 1/2" BSP	12953413
80	1	40	300	510	BSP female 1/2" BSP	12953414
80	1	40	400	610	BSP female 1/2" BSP	12953415
80	1	40	500	710	BSP female 1/2" BSP	12953416
80	1	40	600	810	BSP female 1/2" BSP	12953417
80	1	50	200	410	BSP female 1/2" BSP	12953418
80	1	50	300	510	BSP female 1/2" BSP	12953419
80	1	50	400	610	BSP female 1/2" BSP	12953420
80	1	50	500	710	BSP female 1/2" BSP	12953421
80	1	50	600	810	BSP female 1/2" BSP	12953422
90	1	40	200	410	BSP female 1/2" BSP	12953423
90	1	40	300	510	BSP female 1/2" BSP	12953424

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Bore mm	Number of extensions	Outer diameter piston rod mm	Stroke mm	Built-in size mm	Oilports	Article
90	1	40	400	610	BSP female 1/2" BSP	12953425
90	1	40	500	710	BSP female 1/2" BSP	12953426
90	1	40	600	810	BSP female 1/2" BSP	12953427
90	1	50	200	410	BSP female 1/2" BSP	12953428
90	1	50	300	510	BSP female 1/2" BSP	12953429
90	1	50	400	610	BSP female 1/2" BSP	12953430
90	1	50	500	710	BSP female 1/2" BSP	12953431
90	1	50	600	810	BSP female 1/2" BSP	12953432
100	1	50	200	420	BSP female 1/2" BSP	12953433
100	1	50	300	520	BSP female 1/2" BSP	12953434
100	1	50	400	620	BSP female 1/2" BSP	12953435
100	1	50	500	720	BSP female 1/2" BSP	12953436
100	1	50	600	820	BSP female 1/2" BSP	12953437
100	1	60	200	420	BSP female 1/2" BSP	12953438
100	1	60	300	520	BSP female 1/2" BSP	12953439
100	1	60	400	620	BSP female 1/2" BSP	12953440
100	1	60	500	720	BSP female 1/2" BSP	12953441
100	1	60	600	820	BSP female 1/2" BSP	12953442

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.