



CUS SA Telescopic cylinders with ball

Characteristics

Type: Telescopic cylinder with ball

Type (DA/SA): Single acting

Max. operating pressure: 180 bar

Front fixation: Ball

Rear fixation: Mounting lugs

Max. load at max. working pressure kg	Number of extensions	Outer diameter piston rod mm	Stroke mm	Built-in size mm	Oilports	Article
3000	2	61/76	500	410	BSP female 1/2" BSP	12558763
3000	2	61/76	600	460	BSP female 1/2" BSP	12558764
3000	2	61/76	700	508	BSP female 1/2" BSP	12558765
3000	3	46/61/76	360	268	BSP female 1/2" BSP	12558766
3000	3	46/61/76	500	314	BSP female 1/2" BSP	12558767
3000	3	46/61/76	600	347	BSP female 1/2" BSP	12558768
3000	3	46/61/76	700	380	BSP female 1/2" BSP	12558769
3000	3	46/61/76	800	414	BSP female 1/2" BSP	12558770
3000	3	46/61/76	900	449	BSP female 1/2" BSP	12558771
3000	3	46/61/76	1050	497	BSP female 1/2" BSP	12558772
5000	3	61/76/91	500	327	BSP female 1/2" BSP	12558773
5000	3	61/76/91	600	360	BSP female 1/2" BSP	12558774
5000	3	61/76/91	700	393	BSP female 1/2" BSP	12558775
5000	3	61/76/91	800	427	BSP female 1/2" BSP	12558776
5000	3	61/76/91	900	460	BSP female 1/2" BSP	12558777
5000	3	61/76/91	1050	510	BSP female 1/2" BSP	12558778
5000	3	61/76/91	1150	543	BSP female 1/2" BSP	12558779
5000	4	46/61/76/91	480	268	BSP female 1/2" BSP	12558780
5000	4	46/61/76/91	600	298	BSP female 1/2" BSP	12558781
5000	4	46/61/76/91	680	318	BSP female 1/2" BSP	12558782
5000	4	46/61/76/91	850	360	BSP female 1/2" BSP	12558783
5000	4	46/61/76/91	1050	435	BSP female 1/2" BSP	12558784
5000	4	46/61/76/91	1150	435	BSP female 1/2" BSP	12558785
5000	5	46/61/76/91/107	500	500	BSP female 1/2" BSP	12558796
5000	5	46/61/76/91/107	700	291	BSP female 1/2" BSP	12558797
5000	5	46/61/76/91/107	850	320	BSP female 1/2" BSP	12558798
5000	5	46/61/76/91/107	1050	361	BSP female 1/2" BSP	12558799
5000	5	46/61/76/91/107	1150	381	BSP female 1/2" BSP	12558800
5000	5	46/61/76/91/107	1250	401	BSP female 1/2" BSP	12558801
5000	5	46/61/76/91/107	1500	451	BSP female 1/2" BSP	12558802
5000	5	46/61/76/91/107	1850	521	BSP female 1/2" BSP	12558803
5000	6	32/46/61/76/91/107	600	251	BSP female 1/2" BSP	12558804
5000	6	32/46/61/76/91/107	850	291	BSP female 1/2" BSP	12558805
5000	6	32/46/61/76/91/107	1050	320	BSP female 1/2" BSP	12558806
5000	6	32/46/61/76/91/107	1150	342	BSP female 1/2" BSP	12558807
5000	6	32/46/61/76/91/107	1250	361	BSP female 1/2" BSP	12558808
8000	4	61/76/91/107	600	313	BSP female 1/2" BSP	12558786
8000	4	61/76/91/107	680	333	BSP female 1/2" BSP	12558787
8000	4	61/76/91/107	850	375	BSP female 1/2" BSP	12558788
8000	4	61/76/91/107	950	400	BSP female 1/2" BSP	12558789
8000	4	61/76/91/107	1050	425	BSP female 1/2" BSP	12558790
8000	4	61/76/91/107	1200	462	BSP female 1/2" BSP	12558791

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Max. load at max. working pressure kg	Number of extensions	Outer diameter piston rod mm	Stroke mm	Built-in size mm	Oilports	Article
8000	4	61/76/91/107	1300	488	BSP female 1/2" BSP	12558792
8000	4	61/76/91/107	1500	538	BSP female 1/2" BSP	12558793
8000	4	61/76/91/107	1700	588	BSP female 1/2" BSP	12558794
8000	4	61/76/91/107	2000	662	BSP female 1/2" BSP	12558795
9000	5	61/76/91/107/127	1000	377	BSP female 1/2" BSP	12558809
9000	5	61/76/91/107/127	1250	427	BSP female 1/2" BSP	12558810
9000	5	61/76/91/107/127	1500	477	BSP female 1/2" BSP	12558811
9000	5	61/76/91/107/127	1700	517	BSP female 1/2" BSP	12558812
9000	5	61/76/91/107/127	1850	547	BSP female 1/2" BSP	12558813
9000	5	61/76/91/107/127	2150	607	BSP female 1/2" BSP	12558814
9000	5	61/76/91/107/127	2500	677	BSP female 1/2" BSP	12558815
10000	6	61/76/91/107/127/146	1500	437	BSP female 3/4" BSP	12558816
10000	6	61/76/91/107/127/146	1700	470	BSP female 3/4" BSP	12558817
10000	6	61/76/91/107/127/146	1900	503	BSP female 3/4" BSP	12558818
10000	6	61/76/91/107/127/146	2150	507	BSP female 3/4" BSP	12558819
10000	6	61/76/91/107/127/146	2600	617	BSP female 3/4" BSP	12558820
12000	5	76/91/107/127/146	1250	433	BSP female 1/2" BSP	12558822
12000	5	76/91/107/127/146	1500	483	BSP female 3/4" BSP	12558823
12000	5	76/91/107/127/146	1850	553	BSP female 3/4" BSP	12558824
12000	5	76/91/107/127/146	2150	613	BSP female 3/4" BSP	12558825
12000	5	76/91/107/127/146	2600	703	BSP female 3/4" BSP	12558826
12000	6	76/91/107/127/146	1000	383	BSP female 3/4" BSP	12558821

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.