



CUS SA Telescopic cylinders with ball heavy P-Series

Characteristics

Type: Telescopic cylinder with ball P-series

Type (DA/SA): Single acting

Max. operating pressure: 180 bar

Front fixation: Ball

Rear fixation: Mounting lugs

Max. load at max. working pressure kg	Number of extensions	Outer diameter piston rod mm	Stroke mm	Built-in size mm	Oilports	Article
12000	4	72/91/107/127	1000	427	BSP female 1/2" BSP	12558827
12000	4	72/91/107/127	1200	477	BSP female 3/4" BSP	12558828
12000	4	72/91/107/127	1480	547	BSP female 1/2" BSP	12558829
12000	4	72/91/107/127	1720	607	BSP female 1/2" BSP	12558830
12000	4	72/91/107/127	2000	677	BSP female 1/2" BSP	12558831
12000	7	61/76/91/107/127/146/166	1500	412	BSP female 3/4" BSP	12558832
12000	7	61/76/91/107/127/146/166	1750	447	BSP female 3/4" BSP	12558833
12000	7	61/76/91/107/127/146/166	2100	497	BSP female 3/4" BSP	12558834
12000	7	61/76/91/107/127/146/166	2600	567	BSP female 3/4" BSP	12558835
12000	7	61/76/91/107/127/146/166	3000	627	BSP female 3/4" BSP	12558836
12000	7	61/76/91/107/127/146/166	3500	697	BSP female 3/4" BSP	12558837
18000	4	91/107/127/146	1000	445	BSP female 3/4" BSP	12558838
18000	4	91/107/127/146	1200	495	BSP female 3/4" BSP	12558839
18000	4	91/107/127/146	1480	565	BSP female 3/4" BSP	12558840
18000	4	91/107/127/146	1720	625	BSP female 3/4" BSP	12558841
18000	4	91/107/127/146	2000	695	BSP female 3/4" BSP	12558842
18000	4	91/107/127/146	2400	795	BSP female 3/4" BSP	12558843
18000	6	72/91/107/127/146/166	1500	453	BSP female 3/4" BSP	12558844
18000	6	72/91/107/127/146/166	1800	503	BSP female 3/4" BSP	12558845
18000	6	72/91/107/127/146/166	2220	573	BSP female 3/4" BSP	12558846
18000	6	72/91/107/127/146/166	3000	703	BSP female 3/4" BSP	12558848
18000	6	72/91/107/146/166	2600	633	BSP female 3/4" BSP	12558847
18000	6	72/91/107/146/166	3300	753	BSP female 3/4" BSP	12558849
18000	6	72/91/107/146/166	3600	803	BSP female 3/4" BSP	12558850
20000	5	91/107/127/146/166	1250	451	BSP female 3/4" BSP	12558851
20000	5	91/107/127/146/166	1500	501	BSP female 3/4" BSP	12558852
20000	5	91/107/127/146/166	1850	571	BSP female 3/4" BSP	12558853
20000	5	91/107/127/146/166	2150	631	BSP female 3/4" BSP	12558854
20000	5	91/107/127/146/166	2500	701	BSP female 3/4" BSP	12558855
20000	5	91/107/127/146/166	2750	751	BSP female 3/4" BSP	12558856
20000	5	91/107/127/146/166	3000	801	BSP female 3/4" BSP	12558857
22000	4	107/127/146/166	1000	464	BSP female 3/4" BSP	12558858
22000	4	107/127/146/166	1500	584	BSP female 3/4" BSP	12558860
22000	4	107/127/146/166	1720	644	BSP female 3/4" BSP	12558861
22000	4	107/127/146/166	2000	714	BSP female 3/4" BSP	12558862
22000	4	107/127/146/166	2200	764	BSP female 3/4" BSP	12558863
22000	4	107/127/146/166	2400	814	BSP female 3/4" BSP	12558864
22000	4	107/127/147/166	1200	514	BSP female 3/4" BSP	12558859

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.