



16B-1 Sprocket for taper lock, hardened teeth

Characteristics

Series: Sprocket TL

Type: 16B-1

Norm	Pitch mm	Pitch in	Number of teeth	Taper Lock	Material	Article
DIN 8187	25.4	1	13	1610	Steel C45 [1.0503]	14432559
DIN 8187	25.4	1	14	1610	Steel C45 [1.0503]	14432560
DIN 8187	25.4	1	15	1610	Steel C45 [1.0503]	14432561
DIN 8187	25.4	1	15	1610	Steel C45 [1.0503]	14432705
DIN 8187	25.4	1	17	2012	Steel C45 [1.0503]	13724932
DIN 8187	25.4	1	18	2517	Steel C45 [1.0503]	14432564
DIN 8187	25.4	1	19	2517	Steel C45 [1.0503]	14078524
DIN 8187	25.4	1	19	2517	Steel C45 [1.0503]	14432706
DIN 8187	25.4	1	21	2517	Steel C45 [1.0503]	14432707
DIN 8187	25.4	1	21	2517	Steel C45 [1.0503]	14432566
DIN 8187	25.4	1	22	2517	Steel C45 [1.0503]	14432567
DIN 8187	25.4	1	23	2517	Steel C45 [1.0503]	14432708
DIN 8187	25.4	1	24	2517	Steel C45 [1.0503]	14432569
DIN 8187	25.4	1	25	2517	Steel C45 [1.0503]	14432570
DIN 8187	25.4	1	25	2517	Steel C45 [1.0503]	14432709
DIN 8187	25.4	1	25	2517	Steel C45 [1.0503]	23548275
DIN 8187	25.4	1	26	2517	Steel C45 [1.0503]	14432571
DIN 8187	25.4	1	27	2517	Steel C45 [1.0503]	14432710
DIN 8187	25.4	1	28	2517	Steel C45 [1.0503]	14432572
DIN 8187	25.4	1	30	2517	Steel C45 [1.0503]	12654996
DIN 8187	25.4	1	30	3020	Steel C45 [1.0503]	14432573
DIN 8187	25.4	1	32	3020	Steel C45 [1.0503]	23548388
DIN 8187	25.4	1	38	3020	Steel C45 [1.0503]	13724958
DIN 8187	25.4	1	45	3020	Steel C45 [1.0503]	14432574
DIN 8187	25.4	1	57	3020	Steel C45 [1.0503]	14432575
DIN 8187	25.4	1	76	3020	Steel C45 [1.0503]	14432576
DIN 8187	25.4	1	95	3020	Steel C45 [1.0503]	14008058
DIN 8187	25.4	1	114	3030	Steel C45 [1.0503]	14432577

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.