



EPRAGRATE Grating GRP ISO-FR CONCAVE

Characteristics

Type: Unsanded surface
Surface: Concave

Construction

- The concave surface of EPRAGRATE grating provides superior slip resistant footing in most environments including wet or oily conditions.

Mesh width	Thickness mm	Width mm	Length mm	Tradename	Article
20x20	30	1000	2967	Epragrate GFK	12710368
20x20	30	1207	3647	Epragrate GFK	12498065
38x38	26	921	3055	Epragrate GFK	12710367
38x38	26	997	1990	Epragrate GFK	11322049
38x38	26	1226	2445	Epragrate GFK	12710366
38x38	30	1220	3660	Epragrate GFK	11611374
38x38	30	1225	2980	Epragrate GFK	11136266
38x38	38	1226	2445	Epragrate GFK	12967007
38x38	38	1226	3666	Epragrate GFK	12710370
38x38	38	1530	3969	Epragrate GFK	11256074
38x38	38	1531	3055	Epragrate GFK	12710372
40x40	38	1000	2000	Epragrate GFK	12710371
50x50	13	1220	3660	Epragrate GFK	11256073

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.