

GUHRING Keyway mill, (2-fluted) type 3663

Design: Type N, DIN 327-D, 30°, with central cut.



Application: Can be used for milling keyways and feather key grooves, dia. tolerance e8 for fit P9.

Characteristics

Type: Keyway cutter

Holding system: Weldon

DIN standard: 327

Tolerance: e8/h10

Type	Diameter	Maximum working length	Shaft diameter	Total length	Holding system	Material	DIN standard	Tolerance	Article
	mm	mm	mm	mm					
Keyway cutter	2.5	5	6	49	Weldon	m42	327	e8/h10	11983462
Keyway cutter	3	5	6	49	Weldon	m42	327	e8/h10	12049237
Keyway cutter	3.5	6	6	50	Weldon	m42	327	e8/h10	11983464
Keyway cutter	4.5	7	6	51	Weldon	m42	327	e8/h10	11983466
Keyway cutter	7	10	10	60	Weldon	m42	327	e8/h10	11983471
Keyway cutter	13	16	12	73	Weldon	m42	327	e8/h10	11983482
Keyway cutter	17	19	16	79	Weldon	m42	327	e8/h10	11983486
Keyway cutter	24	26	25	102	Weldon	m42	327	e8/h10	11983491

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.