

DANFOSS Quick coupling steel H5000 series



Characteristics

Series: H5000

Material: Steel

Surface protection: Zinc coated

Minimum medium temperature (continuous): -20 °C

Maximum medium temperature (continuous): 200 °C

Standard: ISO 7241-A

Type of component	Coupling size (inch)	Connection type	Connection size	Maximum operating pressure	Max. flow rate	Sealing	Article
				bar	l/min		
							9501701
Coupling (female)	1/8"	Internal thread	1/8" BSP cyl.	1000	6.1	NBR	841420
Coupling (female)	1/8"	Internal thread	1/8" BSP cyl.	1000	6.1	NBR	12395166
Coupling (female)	1/8"	Internal thread	M 10x1	1000	6.1	NBR	871729
Coupling (female)	3/8"	Internal thread	3/8" BSP cyl.	600	16.7	NBR	957798
Coupling (female)	3/8"	Internal thread	3/8" BSP cyl.	600	16.7	NBR	965960
Coupling (female)	3/8"	Internal thread	3/8" NPT	600	16.7	NBR	1064390
Coupling (female)	1/2"	Internal thread	1/2" BSP cyl.	500	25.5	NBR	957801
Coupling (female)	1/2"	Internal thread	1/2" BSP cyl.	500	25.5	NBR	965979
Coupling (female)	1/2"	Internal thread	1/2" NPT	500	25.5	NBR	803723
Coupling (female)	1/2"	Internal thread	M 22x1.5	500	25.5	NBR	763632
Coupling (female)	3/4"	Internal thread	3/4" BSP cyl.	400	55	NBR	957836
Coupling (female)	3/4"	Internal thread	3/4" BSP cyl.	400	55	NBR	965987
Coupling (female)	1"	Internal thread	1" BSP cyl.	300	87	NBR	957852
Coupling (female)	1.1/4"	Internal thread	1.1/4" BSP cyl.	200	140	FKM	965685
Coupling (female)	1/4"	Internal thread	1/4" BSP cyl.	400	11.6	NBR	957763
Coupling (female)	1/4"	Internal thread	1/4" BSP cyl.	400	11.6	NBR	12701583
Plug (male)	1/8"	Internal thread	1/8" BSP cyl.	1000	6.1	NBR	841390
Plug (male)	1/8"	Internal thread	M 10x1	1000	6.1	NBR	871737
Plug (male)	3/8"	Internal thread	3/8" BSP cyl.	600	16.7	NBR	957658
Plug (male)	3/8"	Internal thread	3/8" NPT	600	16.7	NBR	1064388
Plug (male)	1/2"	Internal thread	1/2" BSP cyl.	500	25.5	NBR	957828
Plug (male)	1/2"	Internal thread	1/2" NPT	500	25.5	FKM	13607697
Plug (male)	1/2"	Internal thread	1/2" NPT	500	25.5	NBR	803731
Plug (male)	1/2"	Internal thread	M 22x1.5	500	25.5	NBR	763624
Plug (male)	3/4"	Internal thread	3/4" BSP cyl.	400	55	NBR	957844
Plug (male)	1"	Internal thread	1" BSP cyl.	300	87	NBR	957860
Plug (male)	1.1/4"	Internal thread	1.1/4" BSP cyl.	200	140	FKM	965693
Plug (male)	1/4"	Internal thread	1/4" BSP cyl.	400	11.6	NBR	957771

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.