



SKF Straight bushing Maintenance-free Steel/PTFE Series: PCZ

- The PTFE-based sliding surface permits smooth, low-friction operation without lubrication. The presence, or continuous supply of oil or other non-corrosive fluids may be advantageous and improve the performance of these bearings.

Advantages of PTFE composite plain bearings include:

- very good frictional properties
 - high load carrying capacity
 - operation temperatures up to 250°C
 - sliding velocity up to 2 m/s
 - small operating clearance
-
- Applications include:
 - automotive
 - material handling equipment
 - home appliances and consumer goods
 - textile machinery

Characteristics

Series: PCZ

With collar: No

Maintenance: Maintenance-free

Tread material: PTFE

Manufacturer ID	Shaft diameter mm	Outer diameter mm	Width mm	Article
PCZ 1014 E	15.824	18.322	22.2	12121219
PCZ 1212 E	19.05	22.225	19.05	11661758
PCZ 1616 E	25.4	28.575	25.4	23229437

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.