



SKF Flanged bushing Low-maintenance Bronze (CuSn8)/ Bronze (CuSn8) Series: PRMF

- Whether grease or oil is used, a good quality lubricant will reduce friction and wear by separating a bronze bushing from its shaft.

Advantages of wrapped bronze bushings include:

- insensitive to contaminated environments
- resistant to shock loads and vibrations at slow speeds
- good resistance to corrosive environments

Applications include:

- agriculture machinery
- hoisting equipment
- construction machinery
- forestry machinery

Characteristics

Series: PRMF

With collar: Yes

Maintenance: Low-maintenance

Tread material: Bronze

Manufacturer ID	Shaft diameter mm	Outer diameter mm	Width mm	Flange diameter mm	Flange thickness mm	Article
PRMF 202316	20	23	16	30	1.5	23769029
PRMF 252815	25	28	15	35	1.5	23769030
PRMF 252825	25	28	25	35	1.5	23769031
PRMF 303420	30	34	20	45	2	23769032
PRMF 303430	30	34	30	45	2	23769033
PRMF 353935	35	39	35	50	2	23769034
PRMF 404425	40	44	25	55	2	23769035
PRMF 404440	40	44	40	55	2	23769036
PRMF 455045	45	50	45	60	2.5	23769038
PRMF 505550	50	55	50	65	2.5	23769039
PRMF 606560	60	65	60	75	2.5	23769041
PRMF 657060	65	70	60	80	2.5	23769042
PRMF 707570	70	75	70	85	2.5	23769043
PRMF 808540	80	85	40	100	2.5	23769045
PRMF 808580	80	85	80	100	2.5	23769046

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.