



SKF Flanged bushing Requiring maintenance Phosphor-Zinnbronze (CuSn10P)/Phosphor-Zinnbronze (CuSn10P) Series: PBMF

- Solid bronze bushings can be lubricated with either oil or grease. The lubricant not only improves the sliding properties, but also reduces wear and prevents corrosion.

Advantages of solid bronze bushings include:

- insensitive to dirty environments
- resistant to shock loads and vibrations at low speed
- good resistance to corrosive contaminants
- equipped with grooves to retain lubricants

- Applications include:
- construction machinery
- transport equipment
- pulp and papermaking machinery
- offshore equipment

Characteristics

Series: PBMF

With collar: Yes

Maintenance: Requiring maintenance

Tread material: Phosphor-Zinnbronze [CuSn10P]

Manufacturer ID	Shaft diameter	Outer diameter	Width	Flange diameter	Flange thickness	Article
	mm	mm	mm	mm	mm	
PBMF 202615 MIG1	20	26	15	32	3	23768554
PBMF 202820 MIG1	20	28	20	35	4	23768555
PBMF 253525 MIG1	25	35	25	45	5	23768556
PBMF 303820 MIG1	30	38	20	44	4	23768557
PBMF 304030 MIG1	30	40	30	50	5	23768558
PBMF 354535 MIG1	35	45	35	55	5	23768560
PBMF 405030 MIG1	40	50	30	58	5	23768561
PBMF 405040 MIG1	40	50	40	60	6	23768562
PBMF 506050 MIG1	50	60	50	70	6	23768566
PBMF 607540 MIG1	60	75	40	83	7.5	23768567
PBMF 607560 MIG1	60	75	60	85	8	23768568

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.