

INA Flanged bushing Maintenance-free Steel/PTFE Series: EGF..E40



Characteristics

Series: EGF..E40

With collar: Yes

Maintenance: Maintenance-free

Tread material: PTFE

Manufacturer ID	Shaft diameter mm	Outer diameter mm	Width mm	Flange diameter mm	Flange thickness mm	Article
EGF06040-E40-Y	6	8	4	12	1	23228530
EGF06070-E40-Y	6	8	7	12	1	23228532
EGF06080-E40-Y	6	8	8	12	1	23228533
EGF08055-E40-Y	8	10	5.5	15	1	23228535
EGF08075-E40-Y	8	10	7.5	15	1	11671576
EGF08095-E40-Y	8	10	9.5	15	1	11671577
EGF10070-E40-Y	10	12	7	18	1	11671578
EGF10090-E40-Y	10	12	9	18	1	23228542
EGF10120-E40-Y	10	12	12	18	1	23228543
EGF10170-E40-Y	10	12	17	18	1	11671579
EGF12070-E40-Y	12	14	7	20	1	23228547
EGF12090-E40-Y	12	14	9	20	1	23228549
EGF12120-E40-Y	12	14	12	20	1	23228551
EGF12170-E40-Y	12	14	17	20	1	23228553
EGF14120-E40-Y	14	16	12	22	1	23228554
EGF14170-E40-Y	14	16	17	22	1	23228555
EGF15090-E40-Y	15	17	9	23	1	23228556
EGF15120-E40-Y	15	17	12	23	1	23228557
EGF15170-E40-Y	15	17	17	23	1	23228559
EGF16120-E40-Y	16	18	12	24	1	23228561
EGF16170-E40-Y	16	18	17	24	1	11671583
EGF18120-E40-Y	18	20	12	26	1	23228565
EGF18170-E40-Y	18	20	17	26	1	23228566
EGF18220-E40-Y	18	20	22	26	1	23228567
EGF20115-E40-Y	20	23	11.5	30	1.5	11671585
EGF20165-E40-Y	20	23	16.5	30	1.5	23228571
EGF20215-E40-Y	20	23	21.5	30	1.5	11671587
EGF25115-E40-Y	25	28	11.5	35	1.5	11671588
EGF25165-E40-Y	25	28	16.5	35	1.5	23228575
EGF25215-E40-Y	25	28	21.5	35	1.5	23228576
EGF30160-E40-Y	30	34	16	42	2	11671590
EGF30260-E40-Y	30	34	26	42	2	11671591
EGF35160-E40-Y	35	39	16	47	2	11671592
EGF35260-E40-Y	35	39	26	47	2	23228583
EGF40260-E40-Y	40	44	26	53	2	23228585

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.