EWELLIX Shaft support with mounting holesseries LRCB

LRCB/LRCC shaft supports to fit open type linear ball bearing units [ISO series 3]. For heavily loaded linear bearing units and/or long track lengths, we recommend the use of shaft supports to eliminate shaft bending. For these applications, continuous or at least partial support of the shaft is necessary. LRCB/LRCC offers shaft supports for shaft diameters ranging from 12 to 80 mm. There are two types of shaft support: the LRCB with predrilled holes and the LRCC without holes. Note: Shaft supports require the use of open design linear bearing units. To be mounted at the shaft for unlimited axial stroke. Supplied with mounting holes in 600 mm standard length.

Characteristics

Series: LRCB With drilled holes: Yes Material: Aluminium

Manufacturer ID	Shaft diameter	Length	Drilling hole distance	Shaft height	Width	Article
	mm	mm	mm	mm	mm	
LRCB 12	12	600	75	22	40	23773350
LRCB 16	16	600	100	26	45	23773349
LRCB 20	20	600	100	32	52	23773351
LRCB 25	25	600	120	36	57	23773352
LRCB 30	30	600	150	42	69	23773353
LRCB 40	40	600	200	50	73	23773354
LRCB 50	50	600	200	60	84	23773355
LRCB 60	60	600	300	68	94	24024990
LRCB 80	80	600	300	86	116	24024991

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Page 1/1

RC0172_0011_WHA_EN_11.05.2024

R



ERIKS NV

Т