

## SKF Inner Ring with Lubrication hole Series: IR..IS1

Inner rings are typically combined with needle roller and cage assemblies or drawn cup needle roller bearings in applications where the shaft cannot be hardened and ground. Inner rings are available in two series: IR series with or without a lubrication hole and the LR series.

## IR series inner rings:

- are the standard inner rings for needle roller bearings
- are hardened and ground
- have a precision ground raceway surface with a lead-in chamfer on both sides
- are available in some sizes with a lubrication hole (designation suffix IS1)

## LR series inner rings:

- are hardened, and the bore and raceway diameter are ground
- side faces are turned and the edges are smoothed
- can be used to provide a cost-effective bearing arrangement for applications where the larger run-out and width tolerances are less important

## **Characteristics**

Series: IR..IS1

with Lubrication hole: Yes

Manufacturer ID	Inner diameter	Outer diameter	Width	Article
	mm	mm	mm	
IR 8X12X10 IS1	8	12	10	23766148
IR 10X14X12 IS1	10	14	12	23766045
IR 25X30X16 IS1	25	30	16	23766085
IR 40X50X20 IS1	40	50	20	23766108
IR 50X55X20 IS1	50	55	20	23766114

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.



RC0186\_0006\_EN\_18.05.2024