



SKF Shaft locating washer Series: WS

Shaft washers are used primarily with cylindrical roller and cage thrust assemblies but can also be combined with needle roller and cage thrust assemblies. SKF recommends using these washers in high-speed applications where accurate centring of the bearing washers is required.

Features:

- are identified by the prefix WS
- are made of hardened carbon chromium bearing steel
- raceway surfaces are precision ground
- have a ground bore

Characteristics

Series: WS

Manufacturer ID	Inner diameter mm	Outer diameter mm	Width mm	Article
WS 81102	15	28	2.75	23771897
WS 81103	17	30	2.75	23221158
WS 81104	20	35	2.75	23771898
WS 81105	25	42	3	23771899
WS 81106	30	47	3	23771900
WS 81206	30	52	4.25	23771910
WS 81107	35	52	3.5	23771901
WS 81108	40	60	3.5	24004677
WS 81109	45	65	4	24004678
WS 81110	50	70	4	23771902
WS 81111	55	78	5	23771903
WS 81112	60	85	4.75	24004679
WS 81113	65	90	5.25	23771904
WS 81114	70	95	5.25	23771905
WS 81116	80	105	5.75	24004680
WS 81117	85	110	5.75	11614170
WS 81118	90	120	6.5	23771907

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.