



SKF Housing locating washer Series: GS

Housing washers are used primarily with cylindrical roller and cage thrust assemblies but can also be combined with needle roller and cage thrust assemblies. SKF recommends using these washers in high-speed applications where accurate centring of the bearing washers is required.

Features:

- are identified by the prefix GS
- are made of hardened carbon chromium bearing steel
- raceway surfaces are precision ground
- have a ground outside surface

Characteristics

Series: GS

Manufacturer ID	Inner diameter mm	Outer diameter mm	Width mm	Article
GS 81102	16	28	2.75	23765403
GS 81103	18	30	2.75	24003442
GS 81104	21	35	2.75	23765404
GS 81105	26	42	3	23765405
GS 81106	32	47	3	23765406
GS 81206	32	52	4.25	23765416
GS 81107	37	52	3.5	23765407
GS 81108	42	60	3.5	24003443
GS 81208	42	68	5	23765417
GS 81109	47	65	4	23765408
GS 81110	52	70	4	23765409
GS 81111	57	78	5	23765410
GS 81112	62	85	4.75	24003444
GS 81113	67	90	5.25	23765411
GS 81114	72	95	5.25	23765412
GS 81116	82	105	5.75	24003446
GS 81117	87	110	5.75	11614180
GS 81118	92	120	6.5	23765413
GS 81126	132	170	9	23765415

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.