



SKF CARB® Toroidal bearing Tapered bore

CARB® bearings are single row bearings with long, slightly barrel-shaped symmetrical rollers. The outer ring has a torus-shaped raceway with a profile radius extending beyond the centre of the bearing. The inner ring raceway is shaped accordingly. CARB® toroidal roller bearings combine the self-aligning capability of spherical roller bearings with the axial displacement ability of cylindrical roller bearings. CARB® bearings can also have the compact cross section and high load carrying capacity normally associated with needle roller bearings.

They are intended exclusively as non-locating bearings. They can simplify locating/non-locating bearing arrangements because thermal expansion of the shaft can be accommodated within the bearing virtually without friction. Bearing arrangements consisting of a spherical roller bearing in the locating position and a CARB® bearing in the non-locating position provide a space- and weight-saving bearing arrangement with a low cost of ownership. CARB® bearings can reduce noise and vibration levels, for example, in paper machines and fans.

Non-sealed basic design CARB® bearings

Depending on their series and size, standard CARB toroidal roller bearings are manufactured to one of the following basic designs: bearings with a cage and full complement bearings. The load carrying capacity of full complement CARB bearings is considerably higher than that of same-sized bearings with a cage. The majority of CARB bearings are available with either a cylindrical or tapered bore. Depending on the bearing series, the tapered bore has a taper of either 1:12 [designation suffix K] or 1:30 [designation suffix K30].

Characteristics

Series: CARB®

Bore: Tapered bore

With sealing: No

Manufacturer ID	Inner diameter mm	Outer diameter mm	Width mm	Internal clearance	Cage	Article
C 2207 KTN9/C3	35	72	23	C3	Polyamide	23760325
C 2209 KTN9/C3	45	85	23	C3	Polyamide	23760335
C 2209 KTN9	45	85	23	CN (normal)	Polyamide	23760334
C 2210 KTN9/C3	50	90	23	C3	Polyamide	23760341
C 2210 KTN9	50	90	23	CN (normal)	Polyamide	23760340
C 2211 KTN9/C3	55	100	25	C3	Polyamide	23760347
C 2211 KTN9	55	100	25	CN (normal)	Polyamide	23760346
C 2212 KTN9/C3	60	110	28	C3	Polyamide	23760353
C 2212 KTN9	60	110	28	CN (normal)	Polyamide	23760352
C 2213 KTN9/C3	65	120	31	C3	Polyamide	23760360
C 2213 KTN9/C4	65	120	31	C4	Polyamide	13199585
C 2213 KTN9	65	120	31	CN (normal)	Polyamide	23760359
C 2215 K/C3	75	130	31	C3	Steel	23760374
C 2215 K	75	130	31	CN (normal)	Steel	23760373
C 2315 K/C3	75	160	55	C3	Steel	23760428
C 2315 K/C4	75	160	55	C4	Steel	24003203
C 2315 K	75	160	55	CN (normal)	Steel	23760427
C 2216 K/C3	80	140	33	C3	Steel	23760380
C 2216 K/C4	80	140	33	C4	Steel	24003190
C 2216 K	80	140	33	CN (normal)	Steel	23760379
C 2316 K/C3	80	170	58	C3	Steel	23760432
C 2316 K/C4	80	170	58	C4	Steel	24003206
C 2316 K	80	170	58	CN (normal)	Steel	23760431
C 2217 K/C3	85	150	36	C3	Steel	23760386
C 2217 K/C4	85	150	36	C4	Steel	24003193
C 2217 K	85	150	36	CN (normal)	Steel	23760385

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Manufacturer ID	Inner diameter mm	Outer diameter mm	Width mm	Internal clearance	Cage	Article
C 2317 K/C3	85	180	60	C3	Steel	23772548
C 2317 K	85	180	60	CN (normal)	Steel	12121172
C 2218 K/C3	90	160	40	C3	Steel	23760390
C 2218 K/C4	90	160	40	C4	Steel	24003194
C 2218 K	90	160	40	CN (normal)	Steel	23760389
C 2318 K/C3	90	190	64	C3	Steel	23760436
C 2318 K/C4	90	190	64	C4	Steel	24003208
C 2318 K	90	190	64	CN (normal)	Steel	23760435
C 2220 K/C3	100	180	46	C3	Steel	23760394
C 2220 K/C4	100	180	46	C4	Steel	24003196
C 2220 K	100	180	46	CN (normal)	Steel	23760393
C 2320 K/C3	100	215	73	C3	Steel	23760440
C 2320 K/C4	100	215	73	C4	Steel	24003210
C 2320 K	100	215	73	CN (normal)	Steel	23760439
C 2222 K/C3	110	200	53	C3	Steel	23760398
C 2222 K/C4	110	200	53	C4	Steel	24003198
C 2222 K	110	200	53	CN (normal)	Steel	23760397
C 3224 K/C3	120	215	76	C3	Steel	23760485
C 3224 K/C4	120	215	76	C4	Steel	24003238
C 3224 K	120	215	76	CN (normal)	Steel	23760484
C 2226 K/C3	130	230	64	C3	Steel	23760402
C 2226 K/C4	130	230	64	C4	Steel	24003200
C 2226 K/C5	130	230	64	C5	Steel	13199586
C 2226 K	130	230	64	CN (normal)	Steel	23760401
C 2228 K/C3	140	250	68	C3	Steel	23227890
C 2228 K	140	250	68	CN (normal)	Steel	23227881
C 3130 K	150	250	80	CN (normal)	Steel	13530020
C 2230 K/C3	150	270	73	C3	Steel	13530019
C 2230 K	150	270	73	CN (normal)	Steel	13530018
C 4032 K30/C3	160	240	80	C3	Steel	24003255
C 4032 K30/C4	160	240	80	C4	Steel	24003256
C 4032 K30/C4W4	160	240	80	C4	Steel	13199600
C 4032 K30	160	240	80	CN (normal)	Steel	24003254
C 3232 K/C3	160	290	104	C3	Steel	13199591
C 3232 K/C4	160	290	104	C4	Steel	13199592
C 3232 K	160	290	104	CN (normal)	Steel	13199590
C 3036 K/C3	180	280	74	C3	Steel	23760444
C 3036 K/HA3C4	180	280	74	C4	Steel	23228347
C 3036 K/C4	180	280	74	C4	Steel	24003211
C 3036 K	180	280	74	CN (normal)	Steel	23760443
C 3136 K/C3	180	300	96	C3	Steel	24003222
C 3136 K/C4	180	300	96	C4	Steel	24003223
C 3136 K	180	300	96	CN (normal)	Steel	24003221
C 3236 K	180	320	112	CN (normal)	Steel	23760489
C 3038 K/C3	190	290	75	C3	Steel	23760448
C 3038 K/C4	190	290	75	C4	Steel	24003213
C 3038 K	190	290	75	CN (normal)	Steel	23760447
C 3040 K/C3	200	310	82	C3	Steel	23760452
C 3040 K/HA3C4	200	310	82	C4	Steel	24211071
C 3040 K/C4	200	310	82	C4	Steel	24003215
C 3040 K	200	310	82	CN (normal)	Steel	23760451
C 3140 K/C3	200	340	112	C3	Steel	23760465
C 3140 K/C4	200	340	112	C4	Steel	24003225

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Manufacturer ID	Inner diameter	Outer diameter	Width	Internal clearance	Cage	Article
	mm	mm	mm			
C 3140 K/HA3C4	200	340	112	C4	Steel	24003226
C 3140 K	200	340	112	CN (normal)	Steel	23760464
C 3044 K/C3	220	340	90	C3	Steel	23760456
C 3044 K/C4	220	340	90	C4	Steel	24003216
C 3044 K/HA3C4	220	340	90	C4	Steel	23227603
C 3044 K	220	340	90	CN (normal)	Steel	23760455
C 3144 K/C3	220	370	120	C3	Steel	23760469
C 3144 K/HA3C4	220	370	120	C4	Steel	24003229
C 3144 K/C4	220	370	120	C4	Steel	24003228
C 3144 K	220	370	120	CN (normal)	Steel	23760468
C 3148 K/C3	240	400	128	C3	Steel	24003232
C 3148 K/C4	240	400	128	C4	Steel	24003233
C 3148 K/HA3C4	240	400	128	C4	Steel	24003234
C 3148 K	240	400	128	CN (normal)	Steel	24003231
C 3160 K/C3	300	500	160	C3	Steel	13828624
C 3164 KM	320	540	176	CN (normal)	Brass	13387229
						11617240
						13025571
						11617243
						11617350
						11617265
						11617071
						12661507
						24204787
						23228050
						23228053
						12121548
						24201907
						23756003
						24204262

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.