



SKF CARB® Toroidal bearing Tapered bore Full complement

CARB® bearings are single row bearings with long, slightly barrel-shaped symmetrical rollers. The outer ring has a torus-shaped raceway with a profile radius extending beyond the centre of the bearing. The inner ring raceway is shaped accordingly. CARB® toroidal roller bearings combine the self-aligning capability of spherical roller bearings with the axial displacement ability of cylindrical roller bearings. CARB® bearings can also have the compact cross section and high load carrying capacity normally associated with needle roller bearings.

They are intended exclusively as non-locating bearings. They can simplify locating/non-locating bearing arrangements because thermal expansion of the shaft can be accommodated within the bearing virtually without friction. Bearing arrangements consisting of a spherical roller bearing in the locating position and a CARB® bearing in the non-locating position provide a space- and weight-saving bearing arrangement with a low cost of ownership. CARB® bearings can reduce noise and vibration levels, for example, in paper machines and fans.

Non-sealed basic design CARB® bearings

Depending on their series and size, standard CARB toroidal roller bearings are manufactured to one of the following basic designs: bearings with a cage and full complement bearings. The load carrying capacity of full complement CARB bearings is considerably higher than that of same-sized bearings with a cage. The majority of CARB bearings are available with either a cylindrical or tapered bore. Depending on the bearing series, the tapered bore has a taper of either 1:12 [designation suffix K] or 1:30 [designation suffix K30].

Characteristics

Series: CARB®

Bore: Tapered bore

With sealing: No

Manufacturer ID	Inner diameter mm	Outer diameter mm	Width mm	Internal clearance	Article
C 2212 KV	60	110	28	CN (normal)	23760354
C 2213 KV/C3	65	120	31	C3	23760362
C 2213 KV	65	120	31	CN (normal)	23760361
C 4026 K30V	130	200	69	CN (normal)	24003245
C 4028 K30V/C3	140	210	69	C3	23760496
C 4028 K30V/C4	140	210	69	C4	24003249
C 4028 K30V	140	210	69	CN (normal)	23760495
C 4030 K30V/C3	150	225	75	C3	23760500
C 4030 K30V/C4	150	225	75	C4	24003251
C 4030 K30V	150	225	75	CN (normal)	23760499
C 4032 K30V/C3	160	240	80	C3	24003258
C 4032 K30V/C4	160	240	80	C4	24003259
C 4032 K30V	160	240	80	CN (normal)	24003257

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.