

STAUFF Test hose SMS Test 15 (M16x1.5) x Test 15 (M16x1.5)



Characteristics

Coupling material: Steel

Surface protection: Zinc-Nickel Black

Connection type connection 1: Test 15

Connection type connection 2: Test 15

Reinforcement type: Synthetic fibre

Tube material: PA

Cover material: PA

Cover colour: Black

Medium temperature (continuous): -35 / 100 °C

Hose ID (DN)	Outside diameter	Maximum operating pressure	Bending radius	Size of threaded connection 1	Size of threaded connection 2	Length	Minimum burst pressure	Test pressure	Article
	mm	bar	mm			mm	bar	bar	
DN02	5	400	20	M 16x1.5	M 16x1.5	400	1100	600	11361082
DN02	5	400	20	M 16x1.5	M 16x1.5	800	1100	600	11360542
DN02	5	400	20	M 16x1.5	M 16x1.5	1000	1100	600	11359459
DN02	5	400	20	M 16x1.5	M 16x1.5	1500	1100	600	11360919
DN02	5	400	20	M 16x1.5	M 16x1.5	1600	1100	600	11360567
DN02	5	400	20	M 16x1.5	M 16x1.5	3200	1100	600	11360802
DN02	5	400	20	M 16x1.5	M 16x1.5	4000	1100	600	11360359
DN02	5	400	20	M 16x1.5	M 16x1.5	5000	1100	600	11360328
DN02	5	630	20	M 16x1.5	M 16x1.5	200	1900	950	11359486
DN02	5	630	20	M 16x1.5	M 16x1.5	240	1900	950	11360770
DN02	5	630	20	M 16x1.5	M 16x1.5	250	1900	950	11360720
DN02	5	630	20	M 16x1.5	M 16x1.5	300	1900	950	11359781
DN02	5	630	20	M 16x1.5	M 16x1.5	370	1900	950	11360772
DN02	5	630	20	M 16x1.5	M 16x1.5	400	1900	950	939390
DN02	5	630	20	M 16x1.5	M 16x1.5	500	1900	950	11359789
DN02	5	630	20	M 16x1.5	M 16x1.5	600	1900	950	11359791
DN02	5	630	20	M 16x1.5	M 16x1.5	630	1900	950	833967
DN02	5	630	20	M 16x1.5	M 16x1.5	750	1900	950	11360896
DN02	5	630	20	M 16x1.5	M 16x1.5	800	1900	950	939412
DN02	5	630	20	M 16x1.5	M 16x1.5	900	1900	950	11361178
DN02	5	630	20	M 16x1.5	M 16x1.5	1000	1900	950	11359540
DN02	5	630	20	M 16x1.5	M 16x1.5	1200	1900	950	11360134
DN02	5	630	20	M 16x1.5	M 16x1.5	1300	1900	950	11361179
DN02	5	630	20	M 16x1.5	M 16x1.5	1500	1900	950	11359774
DN02	5	630	20	M 16x1.5	M 16x1.5	1600	1900	950	11359776
DN02	5	630	20	M 16x1.5	M 16x1.5	1700	1900	950	11361044
DN02	5	630	20	M 16x1.5	M 16x1.5	1800	1900	950	11361459
DN02	5	630	20	M 16x1.5	M 16x1.5	2000	1900	950	11359541
DN02	5	630	20	M 16x1.5	M 16x1.5	2500	1900	950	11359779
DN02	5	630	20	M 16x1.5	M 16x1.5	3000	1900	950	11359782
DN02	5	630	20	M 16x1.5	M 16x1.5	3200	1900	950	11359783
DN02	5	630	20	M 16x1.5	M 16x1.5	3500	1900	950	11359785
DN02	5	630	20	M 16x1.5	M 16x1.5	4000	1900	950	11359787
DN02	5	630	20	M 16x1.5	M 16x1.5	5000	1900	950	11359790
DN02	5	630	20	M 16x1.5	M 16x1.5	6000	1900	950	11360284
DN02	5	630	20	M 16x1.5	M 16x1.5	7000	1900	950	11359793
DN02	5	630	20	M 16x1.5	M 16x1.5	8000	1900	950	11361317

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Hose ID (DN)	Outside diameter	Maximum operating pressure	Bending radius	Size of threaded connection 1	Size of threaded connection 2	Length	Minimum burst pressure	Test pressure	Article
	mm	bar	mm			mm	bar	bar	
DN02	5	630	20	M 16x1.5	M 16x1.5	10000	1900	950	11361157
DN02	5	630	20	M 16x1.5	M 16x1.5	50000	1900	950	11361156
DN04	8.6	340	40	M 16x1.5	M 16x1.5	240	850	570	11360771
DN04	8.6	340	40	M 16x1.5	M 16x1.5	370	850	570	11360773
DN04	8.6	340	40	M 16x1.5	M 16x1.5	400	850	570	11360760
DN04	8.6	340	40	M 16x1.5	M 16x1.5	1000	850	570	11359773
DN04	8.6	340	40	M 16x1.5	M 16x1.5	1200	850	570	11360863
DN04	8.6	340	40	M 16x1.5	M 16x1.5	3200	850	570	11360753

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.