

STAUFF Test hose SMS Test 15 (M16x1.5) x Test 20 (M16x2)



Characteristics

- Coupling material:** Steel
- Surface protection:** Zinc-Nickel Black
- Connection type connection 1:** Test 15
- Connection type connection 2:** Test 20
- Reinforcement type:** Synthetic fibre
- Tube material:** PA
- Cover material:** PA
- Cover colour:** Black
- Medium temperature (continuous):** -35 / 100 °C

Hose ID (DN)	Outside diameter	Maximum operating pressure	Bending radius	Size of threaded connection 1	Size of threaded connection 2	Length	Minimum burst pressure	Test pressure	Article
	mm	bar	mm			mm	bar	bar	
DN02	5	400	20	M 16x1.5	M 16x2	400	1100	600	11359457
DN02	5	400	20	M 16x1.5	M 16x2	500	1100	600	11360586
DN02	5	400	20	M 16x1.5	M 16x2	630	1100	600	11359456
DN02	5	400	20	M 16x1.5	M 16x2	1000	1100	600	11359455
DN02	5	400	20	M 16x1.5	M 16x2	1500	1100	600	11359848
DN02	5	400	20	M 16x1.5	M 16x2	2000	1100	600	11359849
DN02	5	400	20	M 16x1.5	M 16x2	3000	1100	600	11360501
DN02	5	400	20	M 16x1.5	M 16x2	3200	1100	600	11359850
DN02	5	400	20	M 16x1.5	M 16x2	4000	1100	600	11359851
DN02	5	630	20	M 16x1.5	M 16x2	200	1900	950	11360251
DN02	5	630	20	M 16x1.5	M 16x2	400	1900	950	11360661
DN02	5	630	20	M 16x1.5	M 16x2	800	1900	950	11360136
DN02	5	630	20	M 16x1.5	M 16x2	1500	1900	950	11359798
DN02	5	630	20	M 16x1.5	M 16x2	2500	1900	950	11360058
DN02	5	630	20	M 16x1.5	M 16x2	3000	1900	950	11361437
DN02	5	630	20	M 16x1.5	M 16x2	3200	1900	950	11360059
DN02	5	630	20	M 16x1.5	M 16x2	4000	1900	950	11360060

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.