

STAUFF Test hose SMS Test 15 (M16x1.5) x Gauge adapter BSP



Characteristics

Coupling material: Steel

Surface protection: Zinc-Nickel Black

Connection type connection 1: Test 15

Connection type connection 2: Gauge connection

Reinforcement type: Synthetic fibre

Tube material: PA

Cover material: PA

Cover colour: Black

Medium temperature (continuous): -35 / 100 °C

Hose ID (DN)	Outside diameter	Maximum operating pressure	Bending radius	Size of threaded connection 1	Size of threaded connection 2	Length	Minimum burst pressure	Test pressure	Article
	mm	bar	mm			mm	bar	bar	
DN02	5	630	20	M 16x1.5	1/2" BSP cyl.	1000	1900	950	11361418
DN02	5	630	20	M 16x1.5	1/2" BSP cyl.	3000	1900	950	11361314
DN02	5	630	20	M 16x1.5	1/4" BSP cyl.	200	1900	950	11360237
DN02	5	630	20	M 16x1.5	1/4" BSP cyl.	400	1900	950	11360074
DN02	5	630	20	M 16x1.5	1/4" BSP cyl.	400	1900	950	11360239
DN02	5	630	20	M 16x1.5	1/4" BSP cyl.	630	1900	950	11360240
DN02	5	630	20	M 16x1.5	1/4" BSP cyl.	800	1900	950	11360242
DN02	5	630	20	M 16x1.5	1/4" BSP cyl.	800	1900	950	11360075
DN02	5	630	20	M 16x1.5	1/4" BSP cyl.	1000	1900	950	11360070
DN02	5	630	20	M 16x1.5	1/4" BSP cyl.	1000	1900	950	11360243
DN02	5	630	20	M 16x1.5	1/4" BSP cyl.	1500	1900	950	11360071
DN02	5	630	20	M 16x1.5	1/4" BSP cyl.	1500	1900	950	11360244
DN02	5	630	20	M 16x1.5	1/4" BSP cyl.	2000	1900	950	11360072
DN02	5	630	20	M 16x1.5	1/4" BSP cyl.	2500	1900	950	11360241
DN02	5	630	20	M 16x1.5	1/4" BSP cyl.	4000	1900	950	11360109

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.