



STAUFF Test hose SMS Test 20 (M16x2) x Test 20 (M16x2) 90° elbow

Characteristics

- Coupling material:** Steel
- Surface protection:** Zinc-Nickel
- Connection type connection 1:** Test 20
- Connection type connection 2:** Test 20 90° elbow
- Reinforcement type:** Synthetic fibre
- Tube material:** PA
- Cover material:** PA
- Cover colour:** Black
- Medium temperature (continuous):** -35 / 100 °C

Hose ID (DN)	Outside diameter	Maximum operating pressure	Bending radius	Size of threaded connection 1	Size of threaded connection 2	Length	Minimum burst pressure	Test pressure	Article
	mm	bar	mm			mm	bar	bar	
DN02	5	400	20	M 16x2	M 16x2	400	1100	600	11361238
DN02	5	400	20	M 16x2	M 16x2	800	1100	600	11361043
DN02	5	400	20	M 16x2	M 16x2	1000	1100	600	11360272
DN02	5	400	20	M 16x2	M 16x2	1500	1100	600	11361309
DN02	5	630	20	M 16x2	M 16x2	300	1900	950	11361547

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.