



# STAUFF Test hose SMS Test 20 (M16x2) x Gauge adapter BSP 90° elbow

**Characteristics**

- Coupling material:** Steel
- Surface protection:** Zinc-Nickel
- Connection type connection 1:** Test 20
- Connection type connection 2:** Gauge connection 90° elbow
- Reinforcement type:** Synthetic fibre
- Tube material:** PA
- Cover material:** PA
- Cover colour:** Black
- Medium temperature (continuous):** -35 / 100 °C

| Hose ID (DN) | Outside diameter | Maximum operating pressure | Bending radius | Size of threaded connection 1 | Size of threaded connection 2 | Length | Minimum burst pressure | Test pressure | Article  |
|--------------|------------------|----------------------------|----------------|-------------------------------|-------------------------------|--------|------------------------|---------------|----------|
|              | mm               | bar                        | mm             |                               |                               | mm     | bar                    | bar           |          |
| DN02         | 5                | 400                        | 20             | M 16x2                        | 1/2" BSP cyl.                 | 1500   | 1100                   | 600           | 11360655 |
| DN02         | 5                | 400                        | 20             | M 16x2                        | 1/4" BSP cyl.                 | 2000   | 1100                   | 600           | 11360917 |
| DN02         | 5                | 400                        | 20             | M 16x2                        | 1/4" BSP cyl.                 | 2000   | 1100                   | 600           | 11359890 |
| DN02         | 5                | 400                        | 20             | M 16x2                        | 1/4" BSP cyl.                 | 3000   | 1100                   | 600           | 11361495 |
| DN02         | 5                | 400                        | 20             | M 16x2                        | 1/4" BSP cyl.                 | 4000   | 1100                   | 600           | 11360918 |
| DN02         | 5                | 400                        | 20             | M 16x2                        | 1/4" BSP cyl.                 | 5000   | 1100                   | 600           | 11359894 |
| DN02         | 5                | 630                        | 20             | M 16x2                        | 1/4" BSP cyl.                 | 6800   | 1900                   | 950           | 11360964 |

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.