STAUFF Test hose SMS Standpipe connection x Standpipe connection

Characteristics

Coupling material: Steel

Surface protection: Zinc-Nickel

Connection type connection 1: Standpipe

connection

Connection type connection 2: Standpipe

connection

Reinforcement type: Synthetic fibre

Tube material: PA Cover material: PA Cover colour: Black

Medium temperature (continuous): -35 / 100 °C

Hose ID (DN)	Outside diameter	Maximum operating pressure	Bending radius	Size of threaded connection 1	Size of threaded connection 2	Length	Minimum burst pressure	Test pressure	Article
	mm	bar	mm			mm	bar	bar	
DN02	5	400	20	8S - M16x1.5	8S - M16x1.5	1500	1100	600	11361100
DN02	5	400	20	6S - M14x1.5	6S - M14x1.5	3200	1100	600	11361143

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

E-mail: hydrauliek@eriks.be

PR_RC0204_0053_PB_EN_20.05.2024