



SKF Single-Point automatic lubricator series TLSD

- System 24 Electro-mechanical Single-point automatic lubricator. Reliable automatic lubricator under fluctuating operating temperatures or when the application conditions such as high levels of vibrating, limited space or hazardous environments require a remote mounting. Temperature independent dispense rate
- Maximum discharge pressure of 5 bar over the whole dispensing period
- Suitable for both direct and remote installation
- Transparent reservoir allows visual inspection
- Red-yellow-green LEDs indicate the lubricator's status
- Refill sets include battery pack
- Supplied with support flange for enhanced sturdiness
- SKF DialSet software helps to calculate the correct dispense rate

Characteristics

Series: TLSD

Type: TLSD 250/HP2

Drive mechanism	Container volume ml	Lubricant	Article
			14099767
Electromechanical	125	LGEM 2	12590807
Electromechanical	125	LGHB 2	12590808
Electromechanical	125	LGWA 2	12529794
Electromechanical	125	LHMT 68	12590812
Electromechanical	250	LGEM 2	12590845
Electromechanical	250	LGHB 2	12590846
Electromechanical	250	LGWA 2	12590844
Electromechanical	250	LHMT 68	12590849

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.