



## SKF Extreme pressure (EP) grease LGEP 2

- LGEP 2 is mineral oil based, lithium soap thickened grease with extreme pressure additives. This grease provides good lubrication in general applications subjected to harsh conditions and vibrations. Excellent mechanical stability
- Extremely good corrosion inhibiting properties
- Excellent EP performance

### Typical applications:

- Pulp and paper making machines
- Jaw crushers
- Traction motors for rail vehicles
- Dam gates
- Work roll bearings in steel industry
- Heavy machinery, vibrating screens
- Crane wheels, sheaves
- Slewing bearings



### Characteristics

**Series:** LGEP 2

**Application:** Lubrication - grease

**Temperature range:** -20 / 110 °C

**Colour:** Light Brown

**Dropping point:** > 180 °C

**Thickener:** Lithium

**Base oil type:** Mineral oil

**Norm:** NLGI 2

**DIN standard:** DIN 51825 KP2G-20

**Worked penetration 0.1mm:** 265-295

Volume l	Content kg	Packaging	Article
	1	Can	23766599
	5	Can	23766601
	18	Bucket	23766600
	50	Barrel	23766602
	180	Barrel	12174630
0.42		Cartridge	23766598

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.