



FILTRATION GROUP Low-pressure filter type Pi 2000

Characteristics

Series: Pi 2000

Temperature range [°C]: -30 / 120 °C

Code digit	Size	Max. operating pressure bar	Connection	Valve type	With dirt indicator	Voltage	Article
	40		1/2" BSP cyl.	Bypass 3,5 bar	No		13521714
	40		1/2" BSP cyl.	No bypass	No		13521718
Pi 20004-068	40	63	1/2" BSP cyl.		Optical 2,2 bar		13521719
Pi 20004-069	40	63	1/2" BSP cyl.		Optical/Electrical 2,2 bar	250VAC/200VDC	13521720
Pi 20004-057	40	63	1/2" BSP cyl.	Bypass 3,5 bar	Optical 2,2 bar		13521716
Pi 20004-058	40	63	1/2" BSP cyl.	Bypass 3,5 bar	Optical/Electrical 2,2 bar	250VAC/200VDC	13521717
	63		3/4" BSP cyl.	Bypass 3,5 bar	No		13521722
	63		3/4" BSP cyl.	No bypass	Optical 2,2 bar		13521725
Pi 20006-069	63	63	3/4" BSP cyl.		Optical/Electrical 2,2 bar	250VAC/200VDC	13521726
Pi 20006-057	63	63	3/4" BSP cyl.	Bypass 3,5 bar	Optical 2,2 bar		13521723
Pi 20006-058	63	63	3/4" BSP cyl.	Bypass 3,5 bar	Optical/Electrical 2,2 bar	250VAC/200VDC	13521724
	100		3/4" BSP cyl.	Bypass 3,5 bar	No		13521728
	100		3/4" BSP cyl.	No bypass	No		13521731
	100		3/4" BSP cyl.	No bypass	Optical/Electrical 2,2 bar	250VAC/200VDC	13521733
Pi 20010-068	100	63	3/4" BSP cyl.		Optical 2,2 bar		13521732
Pi 20010-057	100	63	3/4" BSP cyl.	Bypass 3,5 bar	Optical 2,2 bar		13521729
Pi 20010-058	100	63	3/4" BSP cyl.	Bypass 3,5 bar	Optical/Electrical 2,2 bar	250VAC/200VDC	13521730
	160		1.1/4" BSP cyl.	Bypass 3,5 bar	No		13521735
	160		1.1/4" BSP cyl.	No bypass	No		13521738
Pi 20016-068	160	32	1.1/4" BSP cyl.		Optical 2,2 bar		13521739
Pi 20016-069	160	32	1.1/4" BSP cyl.		Optical/Electrical 2,2 bar	250VAC/200VDC	13521740
Pi 20016-057	160	32	1.1/4" BSP cyl.	Bypass 3,5 bar	Optical 2,2 bar		13521736
Pi 20016-058	160	32	1.1/4" BSP cyl.	Bypass 3,5 bar	Optical/Electrical 2,2 bar	250VAC/200VDC	13521737
	250		1.1/4" BSP cyl.	Bypass 3,5 bar	No		13521743
	250		1.1/4" BSP cyl.	No bypass	Optical 2,2 bar		13521747
Pi 20025-060	250	32	1.1/4" BSP cyl.		No		13521746
Pi 20025-069	250	32	1.1/4" BSP cyl.		Optical/Electrical 2,2 bar	250VAC/200VDC	13521748
Pi 20025-057	250	32	1.1/4" BSP cyl.	Bypass 3,5 bar	Optical 2,2 bar		13521744
Pi 20025-058	250	32	1.1/4" BSP cyl.	Bypass 3,5 bar	Optical/Electrical 2,2 bar	250VAC/200VDC	13521745
	400		1.1/4" BSP cyl.	Bypass 3,5 bar	No		13521750
	400		1.1/4" BSP cyl.	Bypass 3,5 bar	No		13521749
	400		1.1/4" BSP cyl.	No bypass	No		13521753
	400		1.1/4" BSP cyl.	No bypass	Optical 2,2 bar		13521754
	400		1.1/4" BSP cyl.	No bypass	Optical/Electrical 2,2 bar	250VAC/200VDC	13521755
Pi 20040-057	400	32	1.1/4" BSP cyl.	Bypass 3,5 bar	Optical 2,2 bar		13521751
Pi 20040-058	400	32	1.1/4" BSP cyl.	Bypass 3,5 bar	Optical/Electrical 2,2 bar	250VAC/200VDC	13521752

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Code digit	Size	Max. operating pressure bar	Connection	Valve type	With dirt indicator	Voltage	Article
	630		Flange connection DN64	Bypass 0,25 bar	No		13521778
	630		Flange connection DN64	Bypass 0,25 bar	Optic		13521775
	630		Flange connection DN64	Bypass 0,25 bar	Optical/Electrical	250VAC/200VDC	13521774
	630		Flange connection DN64	Bypass 3,5 bar	No		13521769
	630		Flange connection DN64	Bypass 3,5 bar	Optical 2,2 bar		13521771
	630		Flange connection DN64	Bypass 3,5 bar	Optical/Electrical 2,2 bar	250VAC/200VDC	13521772
	630		Flange connection DN64	No bypass	No		13521773
	630		Flange connection DN64	No bypass	Optic		13521777
	630		Flange connection DN64	No bypass	Optical 2,2 bar		13521779
	630		Flange connection DN64	No bypass	Optical/Electrical 2,2 bar	250VAC/200VDC	13521780
	630		Flange connection DN64	No bypass	Optical/Electrical	250VAC/200VDC	13521776
	1000		Flange connection DN64	Bypass 0,25 bar	No		13521802
	1000		Flange connection DN64	Bypass 0,25 bar	Optic		13521799
	1000		Flange connection DN64	Bypass 0,25 bar	Optical/Electrical	250VAC/200VDC	13521798
	1000		Flange connection DN64	Bypass 3,5 bar	No		13521794
	1000		Flange connection DN64	Bypass 3,5 bar	Optical 2,2 bar		13521795
	1000		Flange connection DN64	No bypass	No		13521797
	1000		Flange connection DN64	No bypass	Optic		13521801
	1000		Flange connection DN64	No bypass	Optical 2,2 bar		13521803
	1000		Flange connection DN64	No bypass	Optical/Electrical 2,2 bar	250VAC/200VDC	13521804
	1000		Flange connection DN64	No bypass	Optical/Electrical	250VAC/200VDC	13521800
Pi 20100-058	1000	25	Flange connection DN64	Bypass 3,5 bar	Optical/Electrical 2,2 bar	250VAC/200VDC	13521796

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.