



FILTRATION GROUP Spin-on filter type Pi 270

Characteristics

Series: Pi 270

Temperature range [°C]: -10 / 70 °C

Code digit	Size	Max. operating pressure bar	Connection	Valve type	With dirt indicator	Voltage	Article
	80		1.1/2" BSP cyl.	Bypass 0,25 bar	No		13521983
	80		1.1/2" BSP cyl.	Bypass 0,25 bar	Optic		13521980
	80		1.1/2" BSP cyl.	Bypass 0,25 bar	Optical/Electrical	250VAC/200VDC	13521979
	80		1.1/2" BSP cyl.	No bypass	Optic		13521982
	80		1.1/2" BSP cyl.	No bypass	Optical/Electrical	250VAC/200VDC	13521981
	125		1.1/2" BSP cyl.	Bypass 0,25 bar	Optical/Electrical	250VAC/200VDC	13521989
	125		1.1/2" BSP cyl.	No bypass	Optic		13521992
Pi 2728-065	125	1	1.1/2" BSP cyl.		Electrical -200 mbar	250VAC/200VDC	13521991
Pi 2728-062	125	1	1.1/2" BSP cyl.	Bypass 0,25 bar	Optic		13521990

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.